

Blixer® 4 - 1V



D

Number of 200-g portions per service



Amount processed per operation

0.4 - 3 kg

A

SALES FEATURES

The Blixer® 4 - 1V can turn small amounts of cooked or raw ingredients into texture-modified meals (soft, puréed or liquid) in next to no time.

B

TECHNICAL FEATURES

Blixer® 4 - 1V. 230V/50Hz/1 ph. Power: 900 W. Speed: 3,000 rpm. 4.5-l stainless-steel bowl with handle, bowl-base fine-serrated twin-blade assembly plus blade cleaning tool. Totally leakproof lid with scraper arm. 2-15 portions (200 g). Select your options at the back page **F** part.

C

TECHNICAL DATA

Output power	900 W
Electrical datas	230V/50Hz/1ph 5.5 A - plug supplied
Speed	3,000 rpm
Dimensions (LxWxH)	240 x 330 x 480 mm
Rate of recyclability	95 %
Net weight	16 kg
Reference	33209

MARKING

EN 12100-1 and 2 - 2004, EN 60204-1 - 2006,
EN 12852, EN 60529-2000 - IP55 - IP34

E

PRODUCT FEATURES/BENEFITS

MOTOR UNIT

- **Industrial direct-drive (no belt) induction** motor designed for intensive use.
- Power 900 W
- Stainless-steel motor shaft.
- All-metal motor base.
- Magnetic safety system, thermal failsafe and motor brake.
- **Single speed 3,000 rpm.**
- **Pulse function** for greater cutting precision.

BLIXER® FUNCTION

- **4.5-l stainless-steel bowl** with handle for better grip.
- **Bowl-base blade assembly** with two high-strength, stainless-steel, fine-serrated blades for homogeneous processing - even for small amounts.
- **Central lid opening** for adding liquid or solid ingredients during processing.
- High heat- and shock-resistant **see-through lid** to monitor processing from start to finish.
- Leakproof lid and bowl unit with bowl scraper arm and lid wiper.
- All parts are dishwasher-safe and can easily be removed for cleaning.

STANDARD ATTACHMENTS

- 4.5-litre bowl with lid.
- Blixer® arm and lid wiper.
- Stainless steel fine-serrated twin-blade assembly with removable cap for easy cleaning.
- Blade cleaning tool.

Blixer® 4 - 1V

F

OPTIONAL ATTACHMENTS

- Additional bowl, blade assembly, lid and scraper arm unit - Ref. 27338
- Coarse-serrated, twin-blade assembly for grinding and kneading - Ref. 27350
- Additional fine-serrated, twin-blade assembly - Ref. 27349

G

DRAWINGS & DIMENSIONS

230V/50Hz/1 ph - power cord and plug supplied

