



Undercounter Range

C400



C500



Note: external dimensions of the new models differs from older models.



**C400
Model**



**C500
Model**

Dimensions

Width	460mm	600mm
Height	720-750mm	820-850mm
Depth	570mm	600mm
Door Height (when open)	310mm	364mm
Door Depth (when open)	910mm	990mm
Clear Entry Height	312mm	352mm

Hydraulics specification

Water supply connection	G3/4" (3/4"BSP)	G3/4" (3/4"BSP)
Required water pressure min/max	1-10 bar	1-10 bar
Incoming Water temperature min/max	4°C/55°C	4°C/55°C
Drain size	40mm diam.	40mm diam.
Maximum drain height (from machine base)	500mm	600mm
Optional integrated water softener	Yes	Yes

Electrical specification

13 Amp Plug – 1 Phase

Amps required	13A (1 Phase)	13A (1 Phase)
Standard operating voltage	220-240V/1N~/50Hz	220-240V/1N~/50Hz
Total connected load	2.5 kW	2.5 kW

30 Amp – 1 Phase

Amps required	30A (1 Phase)	30A (1 Phase)
Standard Operating Voltage	220-240V/1N~/50Hz	220-240V/1N~/50Hz
Total Connected Load	6.5 kW	6.5 kW

13 Amp – 3 Phase

Amps required	13A (3 Phase)	13A (3 Phase)
Standard Operating Voltage	380-415V/3N~/50Hz	380-415V/3N~/50Hz
Total Connected Load	6.5 kW	6.5 kW

Capacities & Performance

Glasses per rack	16	25
Plates per rack	9	18
Wash Programmes - Glass	1.5 & 2 min. cycles	1.5 & 2 min. cycles
Wash Programmes - Dish	2, 3 & 5 min. cycles	2, 3 & 5 min. cycles
Theoretical max. racks per hour - Glass	40	40
Theoretical max. racks per hour - Dish	30	30
Wash tank capacity	9.5 litres	15 litres
Rinse tank capacity	6.5 litres	6.5 litres
Wash temperature	60 °C	60 °C
Rinse temperature - Glass	70 °C	70 °C
Rinse temperature - Dish	82 °C	82 °C
Water consumption per cycle	2.75 litres	2.75 litres

Other

Weight (Empty)	49.5Kg / 54.5 Kg (WS)	55.8Kg / 60.8 Kg (WS)
Weight (Full)	66Kg / 72.5 Kg (WS)	77.3Kg / 83.8 Kg (WS)
Weight (Packed)	58.3Kg / 63.3 Kg (WS)	63.8Kg / 68.8 Kg (WS)
Optional Inbuilt Water Softener	Yes	Yes