

Door lock

Atosa EBF05 5 Grid Undercounter Blast Chiller/Freezer



The Atosa EBF05 5 Grid Undercounter Blast Chiller/Freezer is constructed with a High Grade Stainless Steel Exterior & Interior. This product has a Blast Chill Capacity of 25 kg and a Blast Freeze Capacity of 15 kg. It has an Internal Food Probe to ensure even temperatures and an Easy Clean recess Door Handle.

- ${\ensuremath{\textcircled{}}} {\ensuremath{\textcircled{}}} {\ensuremath{}} {\ensuremath{\textcircled{}}} {\ensuremath{\textcircled{}}} {\ensuremath{\textcircled{}}} {\ensuremath{\textcircled{}}} {\ensuremath{}} {\ensuremath{\textcircled{}}} {\ensuremath{\\}} {\ensuremath{}} {\ensurem$
- 𝞯 High Grade Stainless Steel Construction Exterior
- ✓ Self-closing and Stay Open door
- ✓ Combined Chiller/Freezer
- 𝐼 Temperature range +90°C to + 3°C in 90 mins Chill
- 𝐼 Temperature range +90°C to −18°C in 240 mins Freeze
- 𝞯 5 x 1/1 GN or 5 x Bakery Trays Compatible

SPECIFICATIONS

| Summary | | Power and Performance | |
|------------------------|-----------------|---------------------------|----------|
| Brand | Atosa | Voltage (V/HZ/PH) | 220/50/1 |
| Model | EBF05 | Power (Watts) | 1300 |
| Shelf Runners Quantity | 5 Grid | Electrical Current (Amps) | 6.5 |
| Material External | Stainless Steel | | |
| Material Internal | Stainless Steel | | |
| Lighting | No | | |

No

| Key Specifications | | Weights and Dimensions | |
|---------------------------|-------------------|-------------------------------|------------------|
| Climate Class | 4 | Blast Chill Capacity | 25 kg |
| Defrost Method | Hot Air Defrost | Blast Freeze Capacity | 15 kg |
| Refrigerant Type / Amount | R290hc / 150g | Net Weight (kg) | 89 kg |
| Inner Temperature (°C) | +3°C to -18°C | Gross Weight (kg) | 110 kg |
| Cooling Method | Ventilated | Exterior Dimension (WxDxH) mm | 750 x 815 x 870 |
| Insulation | Polyurethane foam | Interior Dimension (WxDxH) mm | 610 x 420 x 364 |
| Foaming Material | C5H10 | Packing Dimension (WxDxH) mm | 805 x 880 x 1000 |
| Castors | 4 | | |



