

PANTHER



P8P4PT - Panther 800 Series Free-standing Hot Cupboard - Plain Top - W 1530 mm - 2.5 kW Helping to cater in demanding environments such as cafeterias, canteens and restaurants, the Panther 800 Series Hot Cupboard is perfect for plating and garnishing and as a pass to front of house staff, while it also provides extra workspace or can be used as a mobile workstation.

- Helping to cater in demanding environments such as cafeterias, canteens and restaurants
- Pass through model with removable sliding doors to both sides provide enhanced workflow efficiency
- Fan assisted hot cupboard provides even heat distribution, fast heat up and recovery times, and lower energy usage. Four shelf positions allow adjustment to meet individual needs.
- Fully 1/1 GN compatible hot cupboard for operational efficiency. Units available to take 4 x 1/1 GN containers up to 150mm deep.
- Accurate digital electronic control of the hot cupboard temperature, adjustable between 20 and 99 °C, ensures compliance with food hygiene regulations
- Double skinned construction provides efficient heat retention and a cool to touch exterior - safe and energy efficient. Removable doors and shelves allow access to the fully stainless steel interior for easy cleaning
- Supplied with two heavy duty multi-section chrome plated rod shelves capable of taking the heaviest loads

Summary		Power and Performance	
Summary		Fower and Performance	
Range Name	Panther	Total Power kW	2.5
Power Type	Electric	Temperature Range °C	20 - 99
Unit Type	Free-standing	IP Rating	IP24
Available in UK Only	No	Plate Capacity	396
UK Warranty	2 Years Parts and Labour Warranty	Temperature Control	Electronic
Export Warranty	Contact your local dealer		
GTIN Code	5056105103585		
Key Specifications		Weights and Dimensions	
Number of Shelves included	2	Unit Height (External) mm	900
Number of Shelf Positions	4	Unit Width (External) mm	1530
Heated Base	Yes	Unit Depth (External) mm	850
Heated Gantry	No	Height (Internal) mm	432
Static or Mobile	Mobile	Width (Internal) mm	1345
		Depth (Internal) mm	512
		Shelf Dimensions Width mm	1286
		Shelf Dimensions Depth mm	512
		Net Weight Kg	141
Supply Connections		Shipping	
Requires Installation	No	Packed Weight Kg	166
Requires Electrical Supply	Yes	Packed Height cm	110
UK 3 Pin Plug	Yes	Packed Width cm	155
Requires Hardwiring	No	Packed Depth cm	90
Electrical Supply Rating Watts	2,500		
Single Phase Amps	10.9		
Single Phase Voltage	230		





Available Options

Overshelf or Gantry

PG4APG4A - Ambient GantryPG4HPG4H - Heated Gantry

PS4A1 PS4A1 - 1 Ambient Overshelf
PS4A2 PS4A2 - 2 Ambient Overshelves
PS4A3 PS4A3 - 3 Ambient Overshelves
PS4H1 PS4H1 - 1 Heated Overshelf
PS4H2 PS4H2 - 2 Heated Overshelves

PS4H3 - 3 Heated Overshelves

Door Locks

PS4H3

PDL4 - Lockable Door

Corner Guards

PCG - Corner Guards [Set of Four]

Legs/Castors

PLK - Legs[non chargeable]


Available Accessories


PLK/S PANTHER LEG KIT FOR CONVERSION IN THE FIELD

Technical Picture













Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 503250

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm

