



PRODUCT OPTIONS AND ACCESSORIES

- DP10 DESCALER POWDER
- FC04 EBFX WATER FILTER - FROM 2015

The M7F enables end users to benefit from a quality UK manufactured product at a competitive price.

The boiler utilises our popular FilterFlow cartridges and is connected to the mains water supply to provide end users with a continuous stream of top quality boiling water.

For ease of installation the boilers come with a UK 3 pin plug and are fixed to the wall with just three screws.

PRODUCT FEATURES

- High quality boiling water on tap 24 hours a day
- Wall mounted, compact design
- Easy installation – UK 3 pin plug and three screws
- Built-in water filtration system improves water quality
- High volume, easy change FilterFlow cartridge
- Adjustable water temperature from 70° - 96°C
- Precise electronic temperature control system
- LCD information panel
- Enhanced multi-level diagnostics

A/A FILE NUMBER:

ITEM NUMBER:



LINCAT FILTERFLOW MF WALL MOUNTED AUTOMATIC FILL BOILER - 7.5L CAPACITY - 3.0 KW

MODEL: M7F

WEIGHTS & DIMENSIONS

Width	340 mil
Depth	269 mil
Height	563 mil
Weight	11.6 kg

SHIPPING DETAILS

Ship Width	41 cm
Ship Depth	63 cm
Ship Height	35 cm
Ship Weight	12.76 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

WATER, PLUMBING, AND DRAINAGE SPECS

Water Line Required	Yes
Water Connection Source Type	Water Main
Water Inlet Size	0.75 in
Water Inlet Pressure Minimum	1 Bar
Water Inlet Pressure Maximum	8 Bar
Drain Line Required	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	UK 3-Pin Plug
Electrical Total Amperage	13 A	Number of Electrical Plugs	1
Electrical Volts	230V	Electrical Connection Type	Cord and Plug
Electrical Total Wattage	3000 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	3 kW	Dedicated Circuit Required	No
Electrical Phase	1-Phase	Electrical Remarks	Single



LINCAT FILTERFLOW MF WALL MOUNTED AUTOMATIC FILL
BOILER - 7.5L CAPACITY - 3.0 KW

MODEL: M7F

ADDITIONAL SPECIFICATIONS

Capacity (Volume)	8 l	Rapid Draw Off Hot	8 l
Construction Materials	Stainless Steel	Rapid Draw Off Hot Cups	38 C
Control Type	Electronic	Ventless Cooking Technology	No
Hourly Hot Water Output	28 l	Temperature Maximum	96 °C
Hourly Number of Hot Cups	140	Temperature Minimum	70 °C

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

