

LINCAT OPUS ELECTRIC FREE-STANDING TWIN TANK FRYER - 2 BASKETS - W 600 MM - 24.0 KW

MODEL: 0E8113



Fry delicious food accurately with this Opus 800 Twin-Tank Free Standing Electric Fryer which comes with two independent fryer tanks for greater versatility. Boasting a precise thermostatic control, the fryer is ideal for a variety of busy commercial kitchens, whether it's a large pub or a restaurant. The hinged, lift out element with safety interlock makes it easy to access and clean the tank.

Opus 800

PRODUCT OPTIONS AND ACCESSORIES

- OF2 Oil filter kit size 2
- LK02 OPUS 350 LEG KIT
- OA8954 SPLASHGUARD FOR OPUS 800 ELECTRIC FRYERS

PRODUCT FEATURES

- Two independent fryer tanks for greater versatility
- Accurate thermostatic control up to 190°C for consistent results and safe operation
- Hinged, lift out element, with safety interlock for easy tank access and cleaning







LINCAT OPUS ELECTRIC FREE-STANDING TWIN TANK FRYER - 2 **BASKETS - W 600 MM - 24.0 KW**

MODEL: 0E8113

| WEIGHTS & DIMENSIONS | |
|----------------------|----------|
| Width | 600 mil |
| Depth | 800 mil |
| Height | 1020 mil |
| Weight | 99 kg |

| SHIPPING DETAILS | |
|----------------------------|-------------------------|
| Ship Width | 70 cm |
| Ship Depth | 85 cm |
| Ship Height | 122 cm |
| Ship Weight | 108.9 kg |
| Number of Shipment Parcels | 1 |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product | No |
| Returnable Item | No |

PRODUCT CERTIFICATIONS



| ENERGY SPECS | |
|----------------------------|--|
| Primary Energy Source Type | Electricity |
| Electrical Amps | L1/L2/L3= 34.8 [1 cab]; L1/L2/L3= 2 x 17.4 [2 cab] |
| Electrical Voltage | 400 volts |
| Electrical Watts | 24000 |
| Electrical Phase | Three |
| Kilowatts | 24 kW |

| Number of Electrical Conductor Wires | 1 |
|--------------------------------------|------------------|
| Electrical Connection Type | Direct Hardwired |
| Electrical Plug Type | Hardwired |
| Number of Electrical Plugs | Not Applicable |
| Dedicated Circuit Required | Yes |
| Energy Saving | No |

| No |
|---|
| Not Applicable |
| Mechanical |
| 64kg chips - 12mm [frozen], 84kg chips - 12mm [chilled] per hour |
| Open Pot |
| No |
| 2 |
| Not Applicable |
| |

| Number of Vats (batteries) | 2 |
|-----------------------------|------------|
| Total Oil Capacity (volume) | 30 l |
| Oil Reclamation | No |
| Oil Temperature Control | Mechanical |
| Pumped Oil Filtration | No |
| Split Pot | Yes |
| Temperature Maximum | 190 °C |
| Temperature Minimum | 90 °C |
| Vat 1 Oil Capacity (volume) | 15 l |
| Vat 2 Oil Capacity (volume) | 15 |

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024







MODEL: 0E8113


BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024

