



Product Code: EP700G 10-152

EcoPro G2 600 Litre Upright Glass Door Refrigerated Cabinet



Features & Benefits

- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet
- Glass door cabinet for easy visibility of stored product, operates up to 32 degrees
- Energy efficiency LED lighting for clear display
- Features Foster's new award-winning +stayclear condenser, revolutionising the effective operation of your refrigeration, ensuring your equipment works more efficiently for longer

External Finish

| | |
|---------------------------------|----------|
| s/steel ext, 304 s/s door | Standard |
| 304 S/S back for island sitting | Option |

Base Fittings

| | |
|--------------|----------|
| Castors 80mm | Standard |
| Legs 150mm | Option |

Electrical, Service & Ecodesign Data

| | |
|----------------------------|----------|
| 230/50/1 | Standard |
| 220/60/1 Electrical Supply | Option |
| Fuse Required | 13 |

Internal Finish

| | |
|-----------|----------|
| aluminium | Standard |
|-----------|----------|

Doors

| | |
|-------|----------|
| Glass | Standard |
|-------|----------|

| | |
|-----------------------|--------|
| Left Hand Hinged Door | Option |
|-----------------------|--------|

Product Extras

| | |
|---------------------|--------|
| Helicoil Mains Lead | Option |
|---------------------|--------|

Shelving

| | |
|---------------------------|--------|
| Additional S/S Trayslides | Option |
|---------------------------|--------|

| | |
|------------------------|--------|
| Additional GN2/1 Shelf | Option |
|------------------------|--------|

Refrigeration

| | |
|---------------------------|----------|
| R134a - Industry Standard | Standard |
|---------------------------|----------|

| | |
|-------------------------------|----------|
| Integral Refrigeration System | Standard |
|-------------------------------|----------|

| | |
|----------------------|--------|
| Less Condensing Unit | Option |
|----------------------|--------|

| | |
|-----------------------------|--------|
| Remote Refrigeration System | Option |
|-----------------------------|--------|

Specification

| | |
|--------------------|-----|
| Dimensions (Width) | 700 |
|--------------------|-----|

| | |
|---------------------|------|
| Dimensions (Height) | 2080 |
|---------------------|------|

| | |
|--------------------|-----|
| Dimensions (Depth) | 820 |
|--------------------|-----|

| | |
|-----------------------|-----|
| Weight (Unpacked, kg) | 121 |
|-----------------------|-----|

| | |
|---------------------|-------|
| Weight (Packed, kg) | 132.6 |
|---------------------|-------|

| | |
|--------------|-----|
| Gross Volume | 600 |
|--------------|-----|

| | |
|----------------|------|
| Noise DbA @ 1M | 64.9 |
|----------------|------|

Footnotes

- Hydrocarbon option not available on glass door models
- 32° C ambient on glass door refrigerator model
- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet



Energy



Quality



Value



Design



Hygiene



After Care