



HOSHIZAKI

PREMIER KPS 120 SG

Blast Chiller/Freezer



1 / 1 GN



2 / 1 GN

ACCESSORIES INCLUDED

N/A

OPTIONAL EXTRAS

N/A

ITEM NUMBER: 975780544

COUNTRY OF ORIGIN: ITALY

PREMIER KPS 120 SG is a HACCP compliant blast chiller/freezer for 1/1 GN (max of 20) and/or 2/1 GN trays (max of 10). Chilling/freezing capacity of 120/60kg. It features IFR control system and a user friendly 7" touch display. Use the preset favorite programs or store your customized cycles. Legs are adjustable 105-150mm.

- 7" touch display with coloured icons
- USB port for download of cooling log data
- Cooling functions: Chilling (soft/hard), freezing (soft/hard), preservation, precooling, infinity
- 'Hot' functions: Thawing, proofing, retarder-prover
- Choose either IFR operation, time or temperature controlled chill/freeze cycle
- Prevent surface freezing damage with the IFR blast chilling function
- Triple-point probe (3 measuring points)
- HACCP: Infinite events up to one year of recording
- Audio-visual HACCP alarms in case of power failure or if a temperature limit is exceeded
- Alarms: Saving up to 40 events
- 10 favorite programs for both blast chilling, blast freezing and retarder proving
- Up to 20 customized cycles can be stored
- Automatic shift to 'storage mode' after the chilling process
- Automatic fan cut-out when door is opened
- Climate class 5 cooling system enduring up to +40°C ambient temperature
- Automatic defrosting
- Easy maintenance with access to condenser without use of tools
- Removable wire rack for 1/1 GN and/or 2/1 GN trays
- Max. Number of pans: 1/1 GN: 20, 2/1 GN: 10
- The internal fan section can be opened for cleaning around and behind the unit
- Right hand hinged door
- Full-height integrated handle
- 90° self-closing door system
- Removable magnetic door gasket

WARRANTY PERIOD

3 Years on Parts & Labour

EXTERIOR

Stainless steel AISI 304

INTERIOR

Stainless steel AISI 304

Refrigerant type: R290 / Refrigerant: 0.3 kg / CO2 equivalent: 0.9 kg

CERTIFICATIONS



Energy consumption - Chilling (kWh/kg)	Energy Consumption - Freezing (kWh/kg)
0.053 kWh/kg	0.165 kWh/kg



HOSHIZAKI

PREMIER KPS 120 SG

TECHNICAL SPECIFICATIONS


GN tray size	Maximum number of trays	Temperature range	Power supply	Climate class	Sound level	Ref. capacity - at -25°C	Chilling capacity (from +70°C to +3°C in 90 minutes)	Freezing capacity (from +70°C to -18°C in 4 hours)
1/1 GN & 2/1 GN	20	-40/+45°C	400V, 3N-/50 Hz	5 (max. ambient 40°C w/ 40% RH)	64 dB	3,130 W	120 kg	60 kg

Distance between guide positions, GN/EN	Dimensions internal (W x D x H)	Maximum depth of gastro pans, GN/EN	Height from base to first guide	Height from ceiling to top guide
530/600	805 mm x 877 mm x 950 mm	650/800	105 mm	105 mm

SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Volume (packed)	Gross weight	Width	Depth	Height including legs (minimum)	Height including legs (maximum)	Net weight
1,120 mm	1,180 mm	2,190 mm	2.894 m ³	305 kg	1,041.5 mm	1,112 mm	1,893 mm	1,938 mm	285 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.



Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige orderSE@hoshizaki.dk
Hoshizaki UK uksales@hoshizaki.uk
Export countries sales.ex@hoshizaki-europe.com
Other countries sales.ex@hoshizaki-europe.com

www.hoshizaki.uk