



PRODUCT OPTIONS AND ACCESSORIES

- DP10 DESCALER POWDER
- BR56 EB6FX WALL BRACKET
- FC04 EBFX WATER FILTER - FROM 2015
- EBHF01 Lincat EB Hands Free Tap Adaptor

Picture the scene. A coach load of holiday makers have just pulled up outside your cafe and they all want hot drinks. Well, with the FilterFlow Automatic Fill Electric Twin-Tap Water Boiler, this scenario is no longer a problem. Twin taps means twice the amount of hot water on tap, 24/7. Teapots can be filled twice as quick. Compact for limited spaces, the boiler comes with a built-in water filtration system which improves the water quality. The eco setting saves energy, and changing the high-volume cartridges is as easy as changing a lightbulb.

PRODUCT FEATURES

- Twin tap version, ideal for the busiest periods
- Narrow 250mm footprint saves valuable counter space without compromising capacity or performance
- Built-in water filtration system improves water quality and reduces scale build-up. High volume, easy change FilterFlow cartridge
- Easily operated from a large, colour touchscreen display. Menu navigation is quick and easy with the temperature and timer simple to adjust
- Eco setting reduces the volume of boiling water by 50% for quieter periods
- 7-day timer allows the boiler to be programmed to switch off overnight or at weekends to conserve energy
- Enhanced diagnostics identify possible causes. The on screen diagnostic information will enable the engineer to identify the parts needed and repair your water boiler at first visit

AIA FILE NUMBER:

ITEM NUMBER:



LINCAT FILTERFLOW COUNTER-TOP AUTOMATIC FILL TWIN-TAP WATER BOILER - W 250 MM - 6.0 KW

MODEL: EB6TFX

WEIGHTS & DIMENSIONS

Width	250 mil
Depth	525 mil
Height	685 mil
Weight	16.2 kg

SHIPPING DETAILS

Ship Width	78.5 cm
Ship Depth	36.6 cm
Ship Height	53 cm
Ship Weight	17.82 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

WATER, PLUMBING, AND DRAINAGE SPECS

Water Line Required	Yes
Water Connection Source Type	Water Main
Water Inlet Size	0.75 in
Water Inlet Pressure	6 Bar
Drain Line Required	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	Hardwired
Electrical Total Amperage	26 A	Number of Electrical Plugs	Not Applicable
Electrical Volts	230V	Electrical Connection Type	Direct Hardwired
Electrical Total Wattage	6000 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	6 kW	Dedicated Circuit Required	No
Electrical Phase	1-Phase	Electrical Remarks	Single

ADDITIONAL SPECIFICATIONS

Capacity (Volume)	22 l	Rapid Draw Off Hot	18 l
Construction Materials	Stainless Steel	Rapid Draw Off Hot Cups	90 C
Control Type	Electronic	Ventless Cooking Technology	No
Hourly Hot Water Output	60 l	Temperature Maximum	98 °C
Hourly Number of Hot Cups	300	Temperature Minimum	70 °C

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

