



Opus 800

With a half ribbed plate option for attractive branding presentation marks, the Opus 800 Electric Ribbed Plate Griddle is designed to create appetizing food accurately. The griddle comes with a precise thermostatic control up to 300°C for consistent results and an economical operation. Perfect for any busy commercial kitchen, it utilizes a maximised cooking area, with the griddle plates to the sides of the unit.

A/A FILE NUMBER:

PRODUCT OPTIONS AND ACCESSORIES

-
- OA8917/C Lincat Opus 800 Free-standing Floor Stand with Castors - for units W 600 mm
- OA8917 Lincat Opus 800 Free-standing Floor Stand with Legs - for units W 600 mm
- OA8972/C Lincat Opus 800 Free-standing Pedestal with Doors and Castors - for units W 600 mm
- OA8972 Lincat Opus 800 Free-standing Pedestal with Doors and Legs - for units W 600 mm
- LK11 OPUS 800 LONG LEG KIT

PRODUCT FEATURES

- Half ribbed plate option for attractive branding presentation marks
- Maximised cooking area, griddle plates sit flush to the sides of the unit
- Precise thermostatic control up to 300°C for consistent results and economical operation

ITEM NUMBER:

WEIGHTS & DIMENSIONS

Width	600 mil
Depth	800 mil
Height	428 mil
Weight	76 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	85 cm
Ship Height	63 cm
Ship Weight	83.6 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Electricity
Electrical Amps	Single Phase 34.8/Three Phase L1=17.4; L2=17.4; L3=N/A
Electrical Voltage	230 volts/400 volts
Electrical Watts	8000
Electrical Phase	Single, Three
Kilowatts	8 kW

Number of Electrical Conductor Wires	1
Electrical Connection Type	Direct Hardwired
Electrical Plug Type	Hardwired
Number of Electrical Plugs	Not Applicable
Dedicated Circuit Required	Yes
Energy Saving	No

ADDITIONAL SPECIFICATIONS

Control Type	Rotary Control Knob
Cooking Area Plate Depth	600 mm
Cooking Area Plate Width	590 mm
Cooking Plate Finish Material Type	Half Grooved Steel Plate
Food Production Rate	96 x 225g [8oz] steaks [chilled] per hour
Legs or Casters	Not Applicable

Lower Platen Surface Type (multi-select)	Smooth and Grooved
Number Of Controls	2
Number of Heating Zones	2
Plate Shape	Rectangle
Plate Thickness	15 mm
Temperature Maximum	300 °C
Temperature Minimum	90 °C
Thermostat Element Location	Under Plate Mount

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

