



Opus 800

PRODUCT OPTIONS AND ACCESSORIES

- LK02 OPUS 350 LEG KIT
- OA8961 SPLASHGUARD VORTECH - OPUS 800

PRODUCT FEATURES

- 97% energy efficiency rating verified in independent BSI tests delivers substantially lower running costs and higher output
- Two stage filtration extends oil life by up to 75% and so reducing oil costs
- Oil can be filtered during or after service even whilst hot
- Convenient electronic ignition
- Externally fired heating gives easy access for cleaning tanks

Fry delicious food and save money and energy at the same time, with this Vortech High Efficiency Opus 800 Free Standing Fryer. Boasting a 97% energy efficiency rating verified in independent BSI tests, the fryer delivers substantially lower running costs and higher output than other fryers. It also comes with a two-stage filtration system which extends oil life by up to 75%, therefore saving you even more money. Designed to meet the needs of any busy commercial kitchen, the powerful, sturdy fryer comes with convenient electronic ignition and filters the oil so that it's ready to use again in less than five minutes.



LINCAT OPUS PROPANE GAS FREE-STANDING SINGLE TANK FRYER WITH PUMPED FILTRATION - 2 BASKETS - W 400 MM - 22.0

MODEL: OG8115/OP/P

WEIGHTS & DIMENSIONS

Width	400 mm
Depth	800 mil
Height	1070 mm
Weight	99.2 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	800 cm
Ship Height	122 cm
Ship Weight	109.12 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Electricity, Gas	Dedicated Circuit Required	Yes
Electrical Amps	4.9	Gas Type	Propane
Electrical Voltage	230 volts	Gas Inlet Size	0.5 in
Electrical Watts	100	Gas Inlet Pressure Required	37 mBar
Electrical Phase	Single	Gas Total BTUs	75064 BTU
Kilowatts	22 kW	Gas Consumption at Max Use Per Hour	1.57 m ³
Number of Electrical Conductor Wires	1	Total Heat Input at Max Use	22 kW, 75064 BTU per hour
Electrical Connection Type	Direct Hardwired	Energy Saving	Yes
Electrical Plug Type	Hardwired		
Number of Electrical Plugs	Not Applicable		

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
January 23, 2024



**LINCAT OPUS PROPANE GAS FREE-STANDING SINGLE TANK
FRYER WITH PUMPED FILTRATION - 2 BASKETS - W 400 MM - 22.0**

MODEL: OG8115/OP/P

ADDITIONAL SPECIFICATIONS

Auto Oil Top-Off	No	Number of Baskets	2
Basket Lift Type	Not Applicable	Number of Burners	2
Control Type	Mechanical	Number of Vats (batteries)	1
Filter Media Type (if applicable)	2-Stage: Fine Tissue Filter and Stainless Steel Filter	Total Oil Capacity (volume)	16 l
Food Production Rate	40kg chips - 12mm [frozen], 51kg chips - 12mm [chilled] per hour	Oil Reclamation	No
Fryer Type	Open Pot	Oil Temperature Control	Mechanical
Integrated Filtration	Yes	Pumped Oil Filtration	Yes
Legs or Casters	Legs	Split Pot	No
		Temperature Maximum	190 °C
		Temperature Minimum	90 °C
		Vat 1 Oil Capacity (volume)	16 l

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.



TECHNICAL DRAWING

