

Service Cabinets

General Purpose, Meat temperature

KICPR60LT



430
STAINLESS
STEEL



PV/PVX - suitable
for fresh meat
storage



Save Control System

Fitted with electronic
controller that optimises
power consumption and
maximises energy saving



KICPRX40LT



FEATURES

White laminated exterior or AISI 430 stainless steel with anti fingerprint treatment

ABS interior with anti-bacterial treatment

5 adjustable shelves as standard

Reversible door

Lock as standard

2 adjustable front feet

Replaceable door gasket

TECHNICAL SPECIFICATIONS

	PR / PRX	PV / PVX
Controller:	Digital controller with temperature display	
Cooling:	Fan assisted	Ventilated
Defrost:	Automatic	Automatic
Refrigerant:	R600a	R600a
Climate Class	4	4
Temperature Range:	+2°C ~ +10°C	-2°C ~ +10°C
Power Supply:	13amp	

MODEL	FINISH	GROSS CAPACITY	EXT. DIMENSIONS (H x W x D mm)	ENERGY RATING	POWER CONSUMPTION	KWH /ANNUM	WEIGHT (kg)	RRP
KICPR40LT	White	380L	1872 x 600 x 620	D	120W	726	78	
KICPR60LT		640L	1872 x 775 x 740	D	120W	817	100	
KICPRX40LT	Stainless Steel	380L	1872 x 600 x 620	D	120W	726	78	
KICPRX60LT		640L	1872 x 775 x 740	D	120W	817	100	
KICPV40MLT	White	380L	1872 x 600 x 620	D	160W	617	86	
KICPV60MLT		640L	1872 x 775 x 740	C	145W	595	103	
KICPVX40MLT	Stainless Steel	380L	1872 x 600 x 620	D	160W	617	86	
KICPVX60MLT		640L	1872 x 775 x 740	C	145W	595	103	

OPTIONAL EXTRAS

Vaporiser kit fitted prior to despatch	£171.00
--	---------

