

Under-counter Control Plus Glass Door Refrigerator 158L

GDPA code PPGR158UK

SKU code **444410527**









Key features

- ✓ 2°C to 8°C temperature range
- Air and core temperature display
- ✓ Represents your vaccine vial
- ✓ External digital controller and temperature display
- ✓ Fitted lock and 2 keys
- Audible and visual temperature alarms
- 5 year warranty as standard











New controller

New updated Controller system for improved user experience. Read, Record, Reset simply with the touch of one button, with no stress of accidentally resetting on the clear digital display.

Dual probe

Greater temperature accuracy given from two temperature probe readings. One probe measuring air temperature and one measuring load (or product) temperature.

Porthole

Factory fitted 16mm porthole enables quick and easy access for any secondary temperature monitoring probes.

Flexible internal storage

Multiple shelf locations along with a wire basket provides a flexible storage solution.

Anti-microbial handle

Powder coated to help prevent cross contamination by inhibiting the growth of microbes.





Specification: Under-counter Control Plus Glass Door Refrigerator 158L

| Gross Capacity (litres) | 158 |
|--|--|
| Net Capacity (litres) | 154 |
| Unit External Width (mm) | 595 |
| Unit External Depth (mm) | 642 |
| Unit External Height (mm) | 850 |
| Product Weight (kg) | 36.25 640 |
| Packed Width (mm) | 660 |
| Packed Depth (mm) | 910 |
| Packed Height (mm) Packed Weight (kg) | 39.75 |
| Country of Origin | UK |
| Internal Dimensions (mm) (WxDxH) | 500 x 450 x 725 |
| Temperature Range | +2°C to +8°C (set point tolerance + or - 2) |
| Colour | White/Green |
| External Finish | Painted Steel |
| Internal Finish | HIPS* |
| Type of plastic | SRL800 (HIPS/ABS mix) |
| Door Finish | Painted Steel / Glass |
| Door Type | Glass |
| Door Style | Hinged, Reversible |
| Door Liner | Flat |
| Door Open Depth (mm) | 1130 |
| Replacement Door Seal | No |
| Open Door Sensor | Yes |
| Lock | Yes, 2 Keys |
| Adjustable Feet (number & position) | 4 - All adjustable |
| Porthole | Yes |
| Porthole Size | 16 mm |
| Porthole Location | Rear LH Corner |
| Temperature Display on Panel | Yes |
| Temperature Alarm | Yes |
| Remote Alarm Contacts | Yes |
| Audible Alarms | Yes |
| Visual Alarms | Yes |
| Number of Shelves | 3 |
| Number of Shelf Positions | 6 |
| Shelf Size (mm) (WxDxH) Shelf Material | 496 x 405 Wire |
| Number of Baskets | 1 |
| Basket Material | Wire |
| Basket Size (mm) (WxDxH) | 485 x 255 x 171 |
| Interior Light | Yes |
| Light Type | LED |
| Light Activation | Door Switch / Controller |
| Fan | Yes - Tangential |
| Spark Free | No |
| Defrost setting | None |
| Controller Type | Digital, External |
| Number of Probes | 2 |
| Probe Type | Air & Load (Glycol Solution) |
| Ambient Temperature Range | 10 to 32 |
| Refrigerant Type | R600a |
| CFC Free | Yes |
| HFC Free | Yes |
| HCFC Free | Yes |
| Ammonia Free | Yes |
| UK 3 Pin Plug | Yes |
| Other Plug Types Available | Yes |
| Voltage Supply | 230v |
| Insulation Thickness (mm) | 55 |
| Insulation Type | High Density Polyurothane Foam |
| Blowing Agent | Cyclopentane |
| Anti Microbial Handle | Yes |
| Wall Brackets Optional Prawer System | No DDC D1591 IK DWD - 444410571 |
| Optional Digital Lock | PPGR158UK-DUK - 444410531 |
| Optional Digital Lock | PPGR158UK-DLK - 444410560 Solid PPSR158UK - 444410526 |
| Other Door Option | |

