



*Opus* 800

Cooking a Full English Breakfast has never been easier than it is with the Opus 800 Electric Griddle, which utilises a maximised cooking area. Two separately controlled heat zones give you the versatility of operating either zone independently when cooking two separate meals simultaneously, or to provide a smaller cooking area during quieter periods. Ideal for any busy commercial kitchen, whatever you decide to cook, from meat, to eggs, to vegetables, you're in control.

#### PRODUCT OPTIONS AND ACCESSORIES

- OA8914/C Lincat Opus 800 Free-standing Floor Stand with Castors - for units W 900 mm
- OA8914 Lincat Opus 800 Free-standing Floor Stand with Legs - for units W 900 mm
- OA8973/C Lincat Opus 800 Free-standing Pedestal with Doors and Castors - for units W 900 mm
- OA8973 Lincat Opus 800 Free-standing Pedestal with Doors and Legs - for units W 900 mm
- LK11 OPUS 800 LONG LEG KIT

#### PRODUCT FEATURES

- Maximised cooking area, griddle plates sit flush to the sides of the unit
- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously

**WEIGHTS & DIMENSIONS**

Width	900 mil
Depth	800 mil
Height	428 mil
Weight	111 kg

**SHIPPING DETAILS**

Ship Width	100 cm
Ship Depth	85 cm
Ship Height	64 cm
Ship Weight	122.1 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

**PRODUCT CERTIFICATIONS**



**ENERGY SPECS**

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	Single Phase 52.2/Three Phase L1=17.4; L2=17.4; L3=17.4	Electrical Connection Type	Direct Hardwired
Electrical Voltage	230 volts/400 volts	Electrical Plug Type	Hardwired
Electrical Watts	12000	Number of Electrical Plugs	Not Applicable
Electrical Phase	Single, Three	Dedicated Circuit Required	Yes
Kilowatts	12 kW	Energy Saving	No

**ADDITIONAL SPECIFICATIONS**

Control Type	Rotary Control Knob	Number Of Controls	2
Cooking Area Plate Depth	890 mm	Number of Heating Zones	2
Cooking Area Plate Width	600 mm	Plate Shape	Rectangle
Cooking Plate Finish Material Type	Steel Plate	Plate Thickness	15 mm
Food Production Rate	160 x 225g [8oz] steaks [chilled] per hour	Temperature Maximum	300 °C
Legs or Casters	Not Applicable	Temperature Minimum	90 °C
Lower Platen Surface Type (multi-select)	Smooth	Thermostat Element Location	Under Plate Mount

### BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

### TECHNICAL DRAWING

