



LGF2500

Glass Door Display Freezer

Product Features

- Fully automatic, fan assisted cooling
- Adjustable shelves
- Self closing doors with stay open feature for ease of loading
- LED interior light with switch (2 LED strips per door)
- Digital controller and temperature display
- Light canopy with switch
- Heated glass door to prevent condensation
- Internal stainless steel base
- Castors and locking feet

The Interlevin LGF range of glass door freezers gives you the option of matching single, double and triple door units (also with matching chiller versions). These robust cabinets come with some great features. Each door has two vertical LED light strips for excellent internal illumination and a large LED light canopy. The base inside the unit is stainless steel for easy cleaning. The carefully designed refrigeration system is energy efficient to keep running costs down. All units come fitted with castors so you can easily move the unit (for cleaning etc), but also with locking feet. All round a versatile quality unit at a great price ideal for frozen foods and ice cream.

Measures and Content

| | | |
|--------------------|----------------|------------|
| Total Display Area | m ² | 0.69 |
| Temperature Range | °C | -25 to -14 |
| Climate Class | | 4 |
| Gross / Net Weight | kg | 140 / 120 |
| Gross / Net Volume | l | 496 / 405 |

Design and Material

| | |
|-----------------------|----------------------------------|
| Door Number & Type | 1 hinged glass door |
| Door Reversible | No |
| Shelves Number & Type | 4 |
| Exterior Finish | White |
| Interior Finish | White |
| Interior Light | 2 x Vertically LED in door frame |

Cooling and Functions

| | |
|--------------------|-----------------------|
| Type of Cooling | Ventilated |
| Type of Defrost | Automatic, electrical |
| Refrigerant | R290 |
| Refrigerant Charge | g120 |
| Thermometer | Yes |

Power and Consumption

| | | |
|---------------------------|----------|----------------|
| Energy Class | | C |
| Energy Consumption | kWh/24h | 7.79 |
| Annual Energy Consumption | kWh/year | 2842 |
| Power | | 13 Amp |
| Max Ambient | | 30°C at 55% RH |
| Input Power | W | 650 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 59 |

Dimensions

| | | |
|----------------------------|-----|------------------|
| Internal Dimension (WxDxH) | mm | 565 x 640 x 1520 |
| External Dimension (WxDxH) | mm | 690 x 800 x 2055 |
| Packed Dimension (WxDxH) | mm | 745 x 860 x 2210 |
| 40ft Container Load | pcs | 44 |



Digital controller



Strong castors