



**PANTHER**

**PRODUCT OPTIONS AND ACCESSORIES**

- PLK/S PANTHER LEG KIT FOR CONVERSION IN THE FIELD

**PRODUCT FEATURES**

- Helping to cater in demanding environments such as cafeterias, canteens and restaurants
- Pass through model with removable sliding doors to both sides provide enhanced workflow efficiency
- Fan assisted hot cupboard provides even heat distribution, fast heat up and recovery times, and lower energy usage. Four shelf positions allow adjustment to meet individual needs.
- Fully 1/1 GN compatible hot cupboard for operational efficiency. Units available to take 5 x 1/1 GN containers up to 150mm deep.
- Accurate digital electronic control of the hot cupboard temperature, adjustable between 20 and 99 °C, ensures compliance with food hygiene regulations
- Double skinned construction provides efficient heat retention and a cool to touch exterior - safe and energy efficient. Removable doors and shelves allow access to the fully stainless steel interior for easy cleaning
- Supplied with two heavy duty multi-section chrome plated rod shelves capable of taking the heaviest loads

AIA FILE NUMBER:

ITEM NUMBER:



# LINCAT PANTHER 800 SERIES FREE-STANDING HOT CUPBOARD - PLAIN TOP - W 1855 MM - 2.5 KW

## MODEL: P8P5PT

### WEIGHTS & DIMENSIONS

|        |          |
|--------|----------|
| Width  | 1855 mil |
| Depth  | 850 mil  |
| Height | 900 mil  |
| Weight | 171 kg   |

### SHIPPING DETAILS

|                          |                         |
|--------------------------|-------------------------|
| Ship Width               | 188 cm                  |
| Ship Depth               | 90 cm                   |
| Ship Height              | 110 cm                  |
| Ship Weight              | 188.1 kg                |
| Ship Method              | LTL Common Carrier      |
| Shipping Package Type    | Pieces                  |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product       | No                      |

### PRODUCT CERTIFICATIONS



### ENERGY SPECS

|                           |          |                                      |               |
|---------------------------|----------|--------------------------------------|---------------|
| Primary Energy Type       | Electric | Electrical Plug Type                 | UK 3-Pin Plug |
| Electrical Total Amperage | 10.9 A   | Number of Electrical Plugs           | 1             |
| Electrical Volts          | 230V     | Electrical Connection Type           | Cord and Plug |
| Electrical Total Wattage  | 2500 W   | Number of Electrical Conductor Wires | 1             |
| Electrical Kilowatts      | 2.5 kW   | Dedicated Circuit Required           | No            |
| Electrical Phase          | 1-Phase  | Electrical Remarks                   | Single        |

### ADDITIONAL SPECIFICATIONS

|                        |                               |                           |         |
|------------------------|-------------------------------|---------------------------|---------|
| Plate Diameter Maximum | 12.75 in                      | Number of Shelf Positions | 4       |
| Plate Diameter Minimum | 11.25 in                      | Number of Shelves         | 2       |
| Cart Style             | Plated Meals and Pans         | Plate Capacity            | 476     |
| Construction Materials | Stainless Steel               | Shelf Depth               | 512 mm  |
| Control Type           | Digital Touch Pad, Electronic | Shelf Width               | 1610 mm |
| Heating System         | Electric                      | Temperature Maximum       | 99 °C   |
| Number of Doors        | 4                             | Temperature Minimum       | 20 °C   |

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated  
March 25, 2025

### BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

### TECHNICAL DRAWING

