

KPS 21 CH



Easy to read LCD control panel. The encoder wheel makes navigation intuitively easy to learn.

- Choose either the IFR operation, time or temperature controlled chill/freeze cycle.

- Prevent surface freezing damage with the IFR blast chilling function.

- HACCP alarms. If a power failure occurs or when a temperature limit is exceeded this will activate an audio-visual alarm.

- Up to 20 customised cycles can be stored.

- Operates as a storage cabinet after the chilling/freezing process has finished.

TECHNICAL INFORMATION

Varenummer	865789950
Category	Blast Chilling
Type	Blast chiller
Line	For 1/1 GN and 60x40 cm
Series	GRAM PROCESS
Equipped with	Right hand hinged door, automatic door closing, removable support for 5 x 1/1 GN trays or bakery trays 60 x 40 cm, multipoint probe with 3 measuring points, HACCP alarms, LCD control panel + encoder for navigation
Temperature range	0/+10°C
Exterior/Interior	Stainless/Stainless
Dim. W x D x H, mm	745 x 720 x 900 mm
Weight, packed	120 kg
Insulation	55 mm (cyclopentane)
Climate class	4
Refrigerant	R 404 A
Ref.capacity at -10°	711 Watt
Connection	230V, 50 Hz
Connection load	900 Watt
Chilling capacity	22 kg from +70°C to 3°C in 90 min.
Sound level	65 dB(A)

