



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE

PRODUCT FEATURES

- Single tank fryer delivering 22.5kg of chips an hour, perfect for pubs, restaurants and care homes
- Front mounted controls for safety
- Thermostatically controlled to give accurate cooking temperatures throughout cooking. Flame failure device and top temperature cut out ensures safe operation.
- Cool zone collects cooking debris - gives cleaner cooking results and saves money by prolonging the life of the oil
- Piezo ignition for easy lighting
- Heavy duty nickel plated baskets for the most demanding of operations
- Internal drain off tap for easy removal of cooking oil

A/A FILE NUMBER:

ITEM NUMBER:



LINCAT SILVERLINK PROPANE GAS FREE-STANDING SINGLE TANK FRYER - 1 BASKET - W 300 MM - 12.0 KW

MODEL: J5/P

WEIGHTS & DIMENSIONS

Width	300 mil
Depth	690 mil
Height	1060 mil
Weight	43 kg

SHIPPING DETAILS

Ship Width	85 cm
Ship Depth	45 cm
Ship Height	122 cm
Ship Weight	47.3 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Gas	Gas Inlet Size	0.5 in
Kilowatts	11.3 kW	Gas Inlet Pressure Required	25 mBar
Electrical Connection Type	Direct Hardwired	Gas Total BTUs	38555 BTU
Electrical Plug Type	Not Applicable	Gas Consumption at Max Use Per Hour	0.81 m ³
Number of Electrical Plugs	Not Applicable	Total Heat Input at Max Use	11.3 kW, 36800 BTU per hour
Gas Type	Propane	Energy Saving	No

ADDITIONAL SPECIFICATIONS

Auto Oil Top-Off	No	Number of Burners	2
Basket Lift Type	Not Applicable	Number of Vats (batteries)	1
Control Type	Mechanical	Total Oil Capacity (volume)	12 l
Food Production Rate	18kg chips -12mm [frozen], 22.5kg chips -12mm [chilled] per hour	Oil Reclamation	No
Fryer Type	Open Pot	Oil Temperature Control	Mechanical
Integrated Filtration	No	Pumped Oil Filtration	No
Number of Baskets	1	Split Pot	No
		Temperature Maximum	190 °C
		Temperature Minimum	110 °C
		Vat 1 Oil Capacity (volume)	12 l

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
January 23, 2024

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

