

## Product Code: FMPRO1200RF 19-104

## 1200mm Pro multideck with rollershutter



## Features & Benefits

- Five display levels maximising capacity
- Energy saving LED lighting is brighter, lasts longer and saves you money
- Additional shelf depth (450mm) delivers increased volume compared to competitor cabinets
- Supplied on roller castors as standard for ease of positioning
- Add 20mm to depth for spacer if product is to be wall-sited (required for air circulation detatchable if not wall-sited)
- 1x top mounted full length LED. On average these last 10x longer than fluorescent lighting and emit a fraction of the heat output.
- · Robust lockable security roller shutter with full solid end panels
- Fully removable shelves and supports for ease of cleaning.
- Removable front cover and slide out condensing unit allows easy access for service, minimising down time. Also our After Sales Support is there when you need us: 2 years parts and labour warranty as standard.

| External Finish                       |          | Internal Finish  |          | Refrigeration                 |          |
|---------------------------------------|----------|--|----------|-------------------------------|----------|
| 304 s/s                               | Standard | 304 s/s  | Standard | R404a - Industry Standard     | Standard |
| Electrical, Service & Ecodesign  Data |          | Specification  |          | Integral Refrigeration System | Standard |
|                                       |          | Width  | 1195     |                               |          |
| 230/50/1                              | Standard | Height   | 1995     |                               |          |
| Fuse Required (A)                     | 13       | Depth  | 775      |                               |          |
|                                       |          | Weight (Unpacked, kg)  | 190      |                               |          |
|                                       |          | Weight (Packed, kg)  | 211.14   |                               |          |
|                                       |          | Add 60mm to depth for spacer if  Depth product is to be wall-sited required for air circulation - detachable if not wall-sited |          |                               |          |
|                                       |          | Noise dBA @ 1m   | TBC      |                               |          |

## Footnotes

- Allow 60mm spacer if product is wall-sited (required for air circulation). Spacers are detachable if product is not to be wall-sited
- Delivery to dealer premises/direct to site on route days free of charge. Delivery and installation to ground floor site as priced see UK price list for conditions











