

Self Contained Ice Machine up to 95 Kg/24h.



Features

- Dual Mode: produces alternatively individually formed Ice-shot glasses (2 cl) or XL Gourmet Ice Cubes (60 grams)
- Up to 2,450 Ice-shot glasses or up to 95 kg (209,5 lbs) daily XL ice cubes production
- Up to 50 kg (110 lbs) ice storage capacity
- Resistant stainless steel exterior
- Air cooled version only; front access condenser air filter, removable and washable
- Front panel mount ON-OFF Switch
- Routine Maintenance alarm light
- Ergonomically designed ice storage access, with disappearing door.
- Door-closing movement dampening system
- Storage bin area vapour-based microbial control system pouch
- Optional PWD System for remote water drain (easy-fit installation)
- Pivoting rear casters
- R-404A CFC-free refrigerant
- Protected by AgION antimicrobial agent




Proximity condenser air filter



Front ON-OFF switch



Easy bin access



Anti-microbial pouch



Pivoting rear wheels

Routine maintenance Alarm

AC 206 ICE SHOT Technologies



		10°: 10°C			21°: 15°C					
		[kg]	[lbs]	N°	[kg]	[lbs]	N°			
AC206 AS Ice Shot Mode		n.a.	n.a.	2450	n.a.	n.a.	2300	50	110	960
AC206 AS XL Cube Mode		95	209,5	1700	89,5	197,5	1600	50	110	960
AC206 WS Ice Shot Mode		n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.
AC206 WS XL Cube Mode		n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.

[WxDxH mm] 1250x620x780/860
 [WxDxH inches] 49x24x30/33
 [w/Hz/ph] 230/50/1
 R 404 A

This product qualifies for the following listings:



Extra Large Gourmet
60 gr.
Ø 44 x H 46 mm



3 Years Warranty

Subject to certain limitations and exclusions

Certified ISO 9001

www.scotsman-ice.it
www.scotsman-ice.com

Models and specifications are subject to change without notice.

Self Contained Ice Machine up to 95 Kg/24h.

FRONT VIEW
780 mm (30 11/16")
860 mm (33 7/8")
1250 mm (49 3/16")
80 mm (3 1/8")

FRONT VIEW (WITH LEGS)
1250 mm (49 3/16")
82 mm (3 1/4")

SIDE VIEW (WITH LEGS)
50 mm (1 15/16")
620 mm (24 7/16")
MIN. FOR UTILITY CONNECTIONS
OPTION TO USE INSTEAD REAR ADJUSTABLE LEGS

REAR VIEW (WITH LEGS)
3/4" GAS
ADJUSTABLE LEGS
413 mm (16 1/4")
449 mm (17 11/16")
49 mm (1 15/16")
139 mm (5 1/2")
209 mm (8 1/4")
269 mm (10 5/8")
347 mm (14 3/4")
3/4" GAS
Ø 20 mm (12/16")

TOP VIEW (LEGS POSITION)
70 mm (2 3/4")
487 mm (19 3/16")
66 mm (2 9/16")
1119 mm (44 1/16")

AC 206 AS Ice shot AIR COOLED

°C / °F	50° / 10°	60° / 15°	70° / 21°	90° / 32°	
10° / 50°	2450	2360	2270	2090	N° Cubes
21° / 70°	2390	2300	2210	2030	N° Cubes
32° / 90°	2230	2140	2050	1870	N° Cubes
38° / 100°	1960	1895	1830	1700	N° Cubes

NOTE:
IF THE UNIT IS INSTALLED AS A BUILT-IN/UNDERCOUNTER,
BETWEEN 5 AND 10 mm ON EACH SIDE MUST BE CONSIDERED
TO ALLOW FOR EASE OF INSTALLATION

AC 206 AS XL AIR COOLED

°C / °F	50° / 10°	60° / 15°	70° / 21°	90° / 32°	
10°	95	91,5	88	81	kg
50°	209,5	201,5	194	178,5	lbs
21°	93	89,5	86	79	kg
70°	205	197,5	189,5	174	lbs
32°	87,5	84	80,5	73,5	kg
90°	193	185	177,5	162	lbs
38°	76,5	74	71,5	66,5	kg
100	168,5	163	157,5	146,5	lbs

AC 206 WS XL WATER COOLED

°C / °F	50° / 10°	60° / 15°	70° / 21°	90° / 32°	
10°	n.a.	n.a.	n.a.	n.a.	kg
50°	n.a.	n.a.	n.a.	n.a.	lbs
21°	n.a.	n.a.	n.a.	n.a.	kg
70°	n.a.	n.a.	n.a.	n.a.	lbs
32°	n.a.	n.a.	n.a.	n.a.	kg
90°	n.a.	n.a.	n.a.	n.a.	lbs
38°	n.a.	n.a.	n.a.	n.a.	kg
100	n.a.	n.a.	n.a.	n.a.	lbs

Minimum	Maximum
10°C (50°F)	40°C (104°F)
5°C (41°F)	35°C (95°F)
-10%	+10%
1 BAR 14 psi	5 BAR 70 psi

	+C° -C°	[Btu/h] [W]	[Ømm ²]	[W]	FUSE	100 Kg [kWh - 100 Kg]	32°C 90°F 21°C 70°F	[l/h] [gal/h]	[kg] [lbs]	[kg] [lbs]
AC206 AS Ice shot	✂	7165 2100	1,5	900	16	25,7	20,4 5,38	83 183	96 211	
AC206 AS XL	✂	7165 2100	1,5	900	16	26,9	12,5 3,8	83 183	96 211	
AC206 WS Ice shot	🌊	7165 2100	1,5	900	16	n.a.	n.a. n.a.	83 183	96 211	
AC206 WS XL	🌊	7165 2100	1,5	900	16	n.a.	n.a. n.a.	83 183	96 211	

IMPORTANT NOTICE:
Models and specifications are subject to change without notice.
This spec sheet is meant for commercial purpose only.
For technical documentation please refer to our service manuals.

www.scotsman-ice.it
www.scotsman-ice.com