



The Refrigeration Experts

## Product specification

---



### EP700L: 600 Ltr Cabinet Freezer

41-106

- ✓ High performance freezer
- ✓ Preserves food quality
- ✓ 33% energy saving
- ✓ In-built safety and hygiene features

#### About the product

Explore the entire award-winning, energy saving [G3 fridge and freezer](#) range.

## Why choose this product

- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer – all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Market leading usable capacity, now supplied with 4 shelves as standard making your money go further – holds more than a conventional fridge
- Operates in ambient temperatures of up to 43°C

# Specification

Technical		Dimensions	
Temperature	Freezer -18/-21°C	Height (mm)	2080
Thermal heat rejection (W)	270	Width (mm)	700
Electrical supply	230/50/1	Depth (mm)	855
Current (A)	1.2	Gross volume (ltr)	600
Power (W)	270	Net volume (ltr)	479.9
Refrigerant mass (g)	80	GN size	2/1
Refrigerant	R290	Gross weight (kg)	115.5
Fuse rating (A)	10	Net weight (kg)	105.5

Build		Energy	
Cabinet type	Standard	Climate Class	5
Finish ext/int	S/S & Alu	Energy grade	B
Number of sections	1	EEI	30.22
Section configuration	Right hinge	AEC (kWh)	1159.32
System	Integral	GWP	3
Leg type	Braked castors	Energy consumption (kWh/24hr)	3.18

## Footnotes

- Castors are not available if product is supplied less condensing unit
- 100mm clearance is required above the cabinet to allow for adequate airflow and service access
- Depth with door open is 1500mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU  
+44 (0)1553 691122 | sales@foster-gamko.com | [www.fosterrefrigerator.com](http://www.fosterrefrigerator.com)

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.