



GRAM GASTRO K 1407 CSG A DL/2D L2

Product series: Gastro

Item number: 951400500

The GRAM GASTRO K 1407 CSG A DL/2D L2 is a with a net internal volume of 179 Ltr.

GRAM Gastro 07 is a series of 1/1 GN workstations, equipped with customizable sections. Furthermore, the highly modular refrigerated counter offers an abundance of practical configuration possibilities.

Temperature Control

Thanks to the Gram air distribution system, temperatures inside the counters always maintain a uniform and correct level.

This includes rapid temperature recovery after every door opening.

Modularity & Scalability

With GRAM GASTRO 07 counters you can put together your individual workplace. Choose your combination of worktop, doors, and drawers, legs /castors/electric elevation, temperature ranges and accessories.

Easy Maintenance

A compact slide-out refrigeration unit for easy maintenance and service access. Removable and easy to clean condenser filters and gaskets.

High Standard in Hygiene

- The counter almost entirely consists of smooth surfaces – the perfect design for easy, quick and thorough cleaning.
- 'Drip Nose' edges on worktops to prevent the ingress of water.
- Worktops with splashbacks to protect your counter from spillage.
- Removable drawer and door gaskets for easy cleaning.
- Pan-shaped inside base with rounded corners to catches fluid.

Allergy-Proof

Counters are made from nickel-free stainless steel.

Ergonomic and practical design

- Anti-tilt shelves and drawers with pull-out stop.
- Extra-long telescopic rails on drawers - GN trays can be lifted in and out without tilting.

SPECIFICATIONS

Temperature range	+2/+12°C	Connection load (Watt)	190
Volume, gross (ltr.)	345	Energy consumption (kWh/Year)	551
Net usable volume (ltr.)	179	Energy Efficiency Class (ISO 22041-2019)	A
Exterior	Stainless	Energy Efficiency Index EEI	24.52
Interior	Stainless	Climate class	5
Dimensions W x D x H (mm)	1289 x 700 x 885/950	Legs / Castors	H = 135/200 mm (L2)
Weight, packed (kg)	140	Refrigerant (kg)	0.097
Insulation (mm)	50 mm (cyclopentane)	CO2 equivalent (kg)	0.291
Refrigerant	R290	GN or Shelf size	1/1 GN
GWP	3	Number of shelves	2
Ref. capacity at -10°C (Watt)	406	Equipped with	Stainless steel solid top, 1 door section with 2 stainless shelves and one drawer section with 2 x 1/2 drawers
Connection	230V, 50 Hz	Door Type	Solid Door