



Electric Chargrills

600mm and 900mm wide

OE8405, OE8406

- Removable, durable, segmented cast iron grids impart attractive branding marks to food
- Independently controlled multiple heat zones (3 in OE8405, and 6 in OE8406) for maximum versatility
- Controlled flaring gives that distinctive chargrilled flavour
- Hinging, interlocked elements and integral water bath makes cleaning easier
- Water bath provides humidity, keeping food succulent and reducing shrinkage



OE8405



OE8406

Chargrill Features

- Hinging, interlocked elements
- Cast iron grids
- Independently controlled heat zone, 3 on OE8405 and 6 on OE8406
- Controlled flaring
- Integral water bath
- Tap fill with front manual top up and 'easy see' water level
- High temperature safety cut-out for protection if water bath runs dry
- Accurate thermostatic control from 90°C to 300°
- Over temperature safety cut out
- Reset button
- Sturdy one piece stainless steel splashguard
- Direct connection to water supply
- Manual fill facility
- Supplied on height adjustable 55-70mm legs

Cleaning and Servicing

- Easy clean stainless steel external finish
- Splashguard to protect surrounding areas
- Sturdy one piece stainless steel splashguard removable for easy cleaning
- Self cleaning branding grids at maximum power
- Integral water bath makes cleaning easier
- Removable, easy clean debris drawers
- Access to all parts from the front and top of unit

Overall Construction

- Permanent laser etched markings on fascia and knobs
- Cast iron grids
- 1.2mm stainless steel welded bull nose and surround
- 1.2mm stainless steel base panel
- 0.8mm stainless steel side panels
- Sturdy increased height one piece stainless steel splashguard
- Welded stainless steel debris collection drawer
- Sits flush to the wall, recess for services

Inclusive Accessories

- Grid cleaning tool
- Branding iron lifting rod

Available Options

• / N Natural Gas or /P Propane Gas

Available Accessories

- OA8972 Pedestal with doors for units 600mm wide
- OA8973 Pedestal with doors for units 900mm wide
- OA8917 Floor stand for units 600mm wide
- OA8914 Floor stand for units 900mm wide







Technical Data


	OE8405	OE8406
Width (mm)	600	900
Depth (mm)	800	800
Overall height (mm)	415	415
Height to hob (mm)	300	300
Cooking area w x d (mm)	540 x 275	625 x 375
Number of individually controlled heat zones	3	6
Heat input per zone (kW)	2.8	2.11
Total electrical power rating (kW)	8.4	12.5
Electrical supply 3N~+e 400V 50-60Hz Current Rating (Amps)	L1 = 12.2 L2 = 12.2 L3 = 12.2	L1 = 18 or 9 x 2 L2 = 18 or 9 x 2 L3 = 18 or 9 x 2
Water connection (BSPT)	1/2"	1/2"
Water pressure (bar)	0.2 - 10	0.2 - 10
Net weight (kg)	57	71
Packed weight (kg)	69	85
Shipping volume (m3)	0.5	0.65
IPX Protection	IPX4	IPX4


OE8405 OE8406
















TEMPORAL SET ON SET ON



☐ International Sales Tel: +44 1522 503250
☐ International Sales e-mail: export@lincat.co.uk



