

Product Code: EP1440M EcoPro G2 1350 Litre Upright Meat Cabinet



Features & Benefits

- Sleek, modern asthetics, robust construction and market leading capacity. 'Smartphone style' fuzzy logic II touch sensitive control panel with high visibility temperature display
- · Low energy refrigerant system with reduced running costs
- · Improved internal fittings for easy cleaning
- Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded
- Operates efficiently in ambients up to 43°C
- Features Foster's new award-winning +stayclear condenser, revolutionising the effective operation of your refrigeration, ensuring your equipment works more efficiently for longer

| External Finish | | |
|---------------------------------------|----------|--|
| s/steel ext, 304 s/s door | Standard | |
| 304 s/s | Option | |
| 304 S/S back for island sitting | Option | |
| Base Fittings | | |
| Castors 80mm | Standard | |
| Legs 150mm | Option | |
| Electrical, Service & Ecodesign Data | | |
| 230/50/1 | Standard | |

| Internal Finish | |
|---------------------|----------|
| aluminium | Standard |
| 304 s/s | Option |
| Doors | |
| Solid | Standard |
| Product Extras | |
| Helicoil Mains Lead | Option |

| Shelving | | |
|-------------------------------|----------|--|
| Additional S/S Trayslides | Option | |
| Additional GN2/1 Shelf | Option | |
| Refrigeration | | |
| R290 - Energy Efficient | Standard | |
| R134a - Industry Standard | Option | |
| Integral Refrigeration System | Standard | |
| Less Condensing Unit | Option | |
| Remote Refrigeration System | Option | |
| Specification | | |
| Dimensions (Width) | 1440 | |
| Dimensions (Height) | 2080 | |
| Dimensions (Depth) | 820 | |
| Weight (Unpacked, kg) | 182.5 | |
| Weight (Packed, kg) | 199.1 | |
| Gross Volume | 1350 | |
| Noise Dba @ 1M | TBC | |

Shelving

Footnotes

220/60/1 Electrical Supply

Fuse Required

kWh (24 hours)

• 150mm castors are not available if product is supplied less condensing unit

Option

13

3.58

- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet











