



The Refrigeration Experts

Product specification



BCT52/26: 52kg/ 26kg Blast Chiller and Freezer

17-283

52kg Blast chiller/freezer cabinet

About the product

Foster Blast Chillers and Freezers safely control the temperature of produce to ensure that food retains its quality, taste and texture.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#)

Learn more about our [Blast Chiller range](#)

Why choose this product

- Chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature up to 90°C for chilling
- Freezing capacity from +70°C to -18°C in less than 240 minutes within specifications
- Dedicated 52Kg blast chiller with occasional 26Kg freeze capacity
- Exceeding UK and European food safety requirements
- High grade 304 exterior and interior the 'gold standard' in performance finishes
- Intuitive touch control panel – just press and go!
- 14 Shelf Positions for GN 1/1 Pans

Specification

Technical		Dimensions	
Refrigerant	R452A	Height (mm)	1790
Electrical supply	230/50/1	Width (mm)	755
Fuse rating (A)	16	Depth (mm)	745
Current (A)	9.8	Gross volume (ltr)	471
Power (W)	2500	Net volume (ltr)	280
Refrigerant mass (g)	1800	Chilling capacity (kg)	52
Thermal heat rejection (W)	2500	Freezing capacity (kg)	26
		Leg type	Braked castors
		GN size	1/1
		Gross weight (kg)	176
		Net weight (kg)	166

Build		Energy	
Finish ext/int	304 S/S & 304 S/S	Climate Class	5
Number of sections	1	Freezing capacity (kg)	26
Section configuration	Right hinge	GWP	2140
System	Integral		

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.