



Green Pizza Prep Counters SPIZ-135 & SPIZ-180



2 YEARS
WARRANTY



2-3 DAY
DELIVERY



UK SERVICE
SUPPORT



MADE IN
THE EU



Specifications

Model	Doors	Gross Capacity	GN Pans	Temperature	Electric Power	Dimensions (mm) Width / Depth / Height			Climate Class	Refrigerant	List Price
SPIZ-135	2	274 ltrs	GN1/4 x 8	-2°C to +8°C	223 kW	1342	700	1052	4	R290a	£1,938
SPIZ-180	3	428 ltrs	GN1/4 x 10	-2°C to +8°C	414 kW	1792	700	1052	4	R290a	£2,338

Key Features

Power supply: 13 amp plug

Hinged doors with automatic return

Stainless Steel interior and exterior

Forced draft evaporator

6 grid level positions for increased loading capacity

Lockable door with replacement gaskets

Intelligent air-circulation system

50mm high-density injected insulation

Green Pizza Prep Counters SPIZ-135 & SPIZ-180



2 YEARS
WARRANTY



2-3 DAY
DELIVERY



UK SERVICE
SUPPORT



MADE IN
THE EU

Efficiency

- “Ventilation Grill” on the front panel keeping the cooling unit system ventilated and running more efficiently.
- Forced draft evaporator with anti-corrosion cover.
- Intelligent Air Circulation system ensures perfect temperature consistency with its innovative airflow design.
- Door switch stops the fan when door is opened to avoid cold air exiting the interior, thus saving energy.
- 50 mm thickness, CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure

Features

- Specially manufactured in high-quality Stainless Steel for intensive professional applications, featuring a very robust design and perfect finishing.
- Stainless Steel doors with ergonomic, full-length, robust, perfectly integrated handle that ensures practical opening of the door that avoids dust and dirt collection.
- Removable guiding rails enable more convenient cleaning operations without additional tools. Placing and adjusting the wire grids at the desired height is possible without using extra rails. Epoxy-coated wire grids, to improve protection, allow storage of different packaging types and have a maximum loading capacity of up to 40kg.
- Removable pull-out/ push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
- Stamped bottom panel with water drain especially designed to make cleaning operations quicker and easier, optimum for hygiene.
- Rounded edge interiors, easier cleaning operations to reduce potential dirt traps.
- 6 grid level positions for increased loading capacity, with a distance of 70mm among them.
- Automatic evaporation of defrost water. Hot gas coming from the compressor is used to automatically evaporate defrost water, instead of by means of heating elements, achieving even less energy consumption and reducing in half defrost time.
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and closes automatically at less than 90°. Door hinges are also reversible allowing the cabinet to be adapted on-site.
- Intuitive digital control allows temperature parameters to be adjusted easily and quickly.
- Luminous start-stop light button.

Contact

Website: www.sterlingpro.co.uk / **Phone:** 01264 560190 / **Email:** sales@sterlingpro.co.uk