

GASTRO K 2207 CSG A DL/DL/DL/DR L2

Product series: Gastro

Item number: 862200021

The GRAM GASTRO K 2207 CSG A DL/DL/DL/DR L2 is a with a net internal volume of 384 Ltr.

GRAM Gastro 07 is a series of 1/1 GN workstations, equipped with customizable sections. Furthermore, the highly modular refrigerated counter offers an abundance of practical configuration possibilities.



Temperature Control

Thanks to the Gram air distribution system, temperatures inside the counters always maintain a uniform and correct level.

This includes rapid temperature recovery after every door opening.

Modularity & Scalability

With GRAM GASTRO 07 counters you can put together your individual workplace. Choose your combination of worktop, doors, and drawers, legs / castors / electric elevation, temperature ranges and accessories.

Easy Maintenance

A compact slide-out refrigeration unit for easy maintenance and service access. Removable and easy to clean condenser filters and gaskets.

High Standard in Hygiene

- The counter almost entirely consists of smooth surfaces – the perfect design for easy, quick and thorough cleaning.
- 'Drip Nose' edges on worktops to prevent the ingress of water.
- Worktops with splashbacks to protect your counter from spillage.
- Removable drawer and door gaskets for easy cleaning.
- Pan-shaped inside base with rounded corners to catches fluid.

Allergy-Proof

Counters are made from nickel-free stainless steel.

Ergonomic and practical design

- Anti-tilt shelves and drawers with pull-out stop.
- Extra-long telescopic rails on drawers - GN trays can be lifted in and out without tilting.

SPECIFICATIONS

Temperature range	+2/+12°C	Power supply	230V, 50 Hz
Volume, gross (ltr.)	668	Connection load (Watt)	235
Net usable volume (ltr.)	384	Energy consumption (kWh/Year)	1.597
Exterior	Stainless	Energy efficiency class	D
Interior	Stainless	Climate class	5 (max. ambient 40°C w/ 40% RH)
Dimensions W x D x H (mm)	2163 x 700 x 885/950	Legs / Castors	H = 135/200 mm (L2)
Weight, packed (kg)	170	Refrigerant (kg)	0,07
Insulation (mm)	50 (cyclopentane)	CO2 equivalent (kg)	0,21
Refrigerant	R290	GN or Shelf size	1/1 GN
GWP	3	Equipped with	Stainless steel solid top, 4 door sections each with 2 stainless shelves
Ref. capacity at -10°C (Watt)	389	Door Type	Insulated Door