



Product Code: EP2/2H

Two door GN2/1 refrigerator counter



The versatile Foster EcoPro G3 counter range offers a huge selection of models, build options and accessories to ensure you find the perfect storage solution for your business.

Features & Benefits

- A reduced footprint– the more compact design of G3 counters allow them to fit in the tightest of kitchen spaces without losing capacity
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer - all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- New and improved 'Airlines' ventilation system cools the compressor which reduces running time, saving you energy
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- High performance cyclopentane foam maintains thermal efficiency for longer
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Supplied with helicoil mains lead, allowing easy movement for cleaning purposes
- Operates efficiently in ambient temperatures of up to 43°C

Shelving

4 shelves (GN2/1)	Standard
Additional S/S Trayslides	Option
Additional GN2/1 Shelf	Option

Refrigeration

R290 - Energy Efficient	Standard
Integral Refrigeration System	Standard
RH Mounted Ref Unit	Option

Specification

Gross volume (ltrs)	495
Refrigerator +1/+4°C	Standard
Width (mm)	1775
Depth (mm)	800
Height (mm)	865

Base Fittings

Castors 80mm	Standard
100mm legs in lieu of castors	Option

Electrical & Service Data

230/50/1	Standard
-----------------	----------

Finish

304 s/s ext & alu int	Standard
304 s/s ext & int	Option
304 S/S back for island sitting	Option

Doors

Solid	Standard
--------------	----------

Product Extras

Helicoil Mains Lead	Option
Splashback	Option
304 S/S Back and Unit Cover	Option


Energy

kWh (24 hours)	1.49
AEC	543
Nett Volume	344.5
Energy Grade	A
Global Warming Potential	3
Energy Efficiency Index	20.35

Footnotes

- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm
- Adequate airflow must be kept around the counter:150mm
- Depth with door open is 1113mm
- 60Hz model supplied as 220v machine with separate transformer for conversion to 115v supply.

Energy Performance Data and information



Application


This appliance is intended for use in ambient temperatures up to 40°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



The Refrigeration Experts

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.