



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- DC01 DONUT CONV KIT DF4/GAS
- CN4 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 450 mm
- SLS4 Lincat Silverlink 600 Free-standing Floor Stand - for units W 450 mm

PRODUCT FEATURES

- Single tank fryer with twin basket operation giving you the flexibility to cook different foods or loads simultaneously, delivering 25kg of chips per hour
- Front mounted controls for safety
- Thermostatically controlled to give accurate cooking temperatures throughout cooking. Flame failure device and top temperature cut out ensures safe operation.
- Cool zone collects cooking debris - gives cleaner cooking results and saves money by prolonging the life of the oil
- Piezo ignition for easy lighting
- Heavy duty nickel plated baskets for the most demanding of operations
- Front drain off tap for easy removal of cooking oil

Fry perfectly crisp and fluffy chips perfectly every single time with the Silverlink 600 Gas Single Tank Counter Top Fryer. Delivering 25kg of chips per hour, the fryer comes with two baskets which gives you the flexibility of cooking different foods or loads simultaneously. With piezo ignition for easy lighting, it's ideal for mobile operations as well as cafes, pubs and restaurants. The fryer comes with an innovative deep cool zone, which collects cooking debris to prolong the life of the oil and therefore save you money. You're always in full control courtesy of the accurate thermostat throughout the entire cooking process, while the flame failure device and top temperature cut out ensures a safe operation.

WEIGHTS & DIMENSIONS

Width	450 mil
Depth	654 mil
Height	415 mil
Weight	30.9 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	55 cm
Ship Height	63.5 cm
Ship Weight	33.99 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Gas	Gas Inlet Size	0.5 in
Kilowatts	10.5 kW	Gas Inlet Pressure Required	35 mBar
Electrical Connection Type	Direct Hardwired	Gas Total BTUs	35826 BTU
Electrical Plug Type	Not Applicable	Gas Consumption at Max Use Per Hour	0.75 m ³
Number of Electrical Plugs	Not Applicable	Total Heat Input at Max Use	10.5 kW, 38600 BTU per hour
Gas Type	Propane	Energy Saving	No

ADDITIONAL SPECIFICATIONS

Auto Oil Top-Off	No	Number of Burners	1
Basket Lift Type	Not Applicable	Number of Vats (batteries)	1
Control Type	Mechanical	Total Oil Capacity (volume)	8 l
Food Production Rate	16kg chips - 12mm [frozen], 25kg chips - 12mm [chilled] per hour	Oil Reclamation	No
Fryer Type	Open Pot	Oil Temperature Control	Mechanical
Integrated Filtration	No	Pumped Oil Filtration	No
Number of Baskets	2	Temperature Maximum	190 °C
		Temperature Minimum	110 °C
		Vat 1 Oil Capacity (volume)	8 l

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

