



BMC3


**Blizzard**

## NEW UPRIGHT HINGED GLASS DOOR MERCHANDISER

### Description

Displaying frozen & chilled goods can often come with some huge draw backs for either your bank balance or visual merchandising, however with the introduction of the new BMF/C range from Blizzard you can rest easy knowing you don't have to sacrifice either.

Featuring a matte black finish, integrated low height rollers for easy installation and maintenance, digital membrane controller, temperature display and self-closing doors, there isn't many reasons that this new range isn't the perfect unit no matter your use case.



### Features

Available in both hinged & sliding door variants

Matt black exterior and interior

Shelf pricing strips

Low energy consumption

5 adjustable black shelves

Internal LED illumination

Self-closing double glazed door with replaceable gasket

Door locks fitted as standard

Low height manouvering rollers

| MODEL | DOORS | SHELVES | GROSS CAPACITY | REFRIGERANT | TEMPERATURE RANGE | DIMENSIONS (mm)      | ENERGY RATING | POWER USAGE | KWH/ANNUM | POWER | WEIGHT (kg) |
|-------|-------|---------|----------------|-------------|-------------------|----------------------|---------------|-------------|-----------|-------|-------------|
| BMF1  | 1     | 5       | 550L           | R290a       | -15°C / -18°C     | H2003 x W750 x D710  | A+ C          | 700         | 3311      | 13amp | 158         |
| BMF2  | 2     | 10      | 1006L          | R290a       | -15°C / -18°C     | H2003 x W1250 x D710 | A+ D          | 1472        | 6377      | 13amp | 270         |
| BMF3  | 3     | 15      | 1564L          | R290a       | -15°C / -18°C     | H2003 x W1880 x D710 | A+ D          | 1680        | 8702      | 13amp | 355         |
| BMC1  | 1     | 5       | 614L           | R290a       | -1°C / +10°C      | H2003 x W750 x D710  | A+ B          | 460         | 913       | 13amp | 141         |
| BMC2  | 2     | 10      | 1081L          | R290a       | -1°C / +10°C      | H2003 x W1250 x D710 | A+ B          | 510         | 1522      | 13amp | 197         |
| BMC3  | 3     | 15      | 1664L          | R290a       | -1°C / +10°C      | H2003 x W1880 x D710 | A+ B          | 700         | 1975      | 13amp | 235         |