



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- SLS9 Lincat Silverlink 600 Free-standing Floor Stand - for units W 900 mm
- HCL9 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 900 mm - 1.0 kW

The Silverlink 600 Electric Chargrill allows you to create that distinctive chargrilled flavour and fire branded appearance without the mess. The water bath keeps food succulent and reduces shrinkage, while the high heat retention cast iron grids ensure your output stays high throughout cooking - there's no need to wait for the grill to recover to cooking temperature. It's perfect for cafes, bars and restaurants.

PRODUCT FEATURES

- Offers the authentic taste and branded appearance of chargrilled food without the need for lava rock
- High heat retention of cast iron grids means there is no waiting for the grill to recover to cooking temperature
- The water bath keeps food succulent and reduces shrinkage, while the high heat retention cast iron grids ensure your output stays high throughout operation
- Hinging interlocked elements and integral water bath makes cleaning easier
- Integral splashguard with water funnel enables refilling of tank without cooling the cooking grid
- High temperature safety cut out for protection if water bath runs dry

WEIGHTS & DIMENSIONS

Width	900 mil
Depth	620 mil
Height	385 mil
Weight	49.4 kg

SHIPPING DETAILS

Ship Width	101.5 cm
Ship Depth	72 cm
Ship Height	59.5 cm
Ship Weight	54.34 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Electricity
Electrical Amps	L1=23.2; L2=23.2; L3=11.6
Electrical Voltage	400 volts
Electrical Watts	13300
Electrical Phase	Three
Kilowatts	13.3 kW

Number of Electrical Conductor Wires	1
Electrical Connection Type	Direct Hardwired
Electrical Plug Type	Hardwired
Number of Electrical Plugs	Not Applicable
Dedicated Circuit Required	Yes
Energy Saving	No

ADDITIONAL SPECIFICATIONS

Control Type	Mechanical, Rotary Control Knob
Cooking Area Plate Depth	400 mm
Cooking Area Plate Width	780 mm
Food Production Rate	105 x 225g [8oz] steaks [chilled] per hour
Grate Type	Cast Iron
Number Of Controls	5
Number of Heating Elements	5
Number of Heating Zones	5

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

