



The Refrigeration Experts

## Product specification



### LR240: 240 Ltr Undercounter Cabinet Freezer

13-125

Reduced width undercounter freezer cabinet

## Features and benefits

- Front breathing refrigeration system makes this model suitable for use in enclosed areas
- Integrated door lock for added security
- High quality magnetic door gasket
- Easy to use microprocessor control with digital display for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- GN1/1 undercounter storage on a small footprint
- Supplied on roller castors as standard for ease of movement and positioning
- Operates in ambient temperatures of up to 40°C (ISO Climate Class 5)

**Refrigerant** R290

**Temperature** Freezer -18/-21°C

**Electrical supply** 230/50/1

**Fuse rating (A)** 10

**Current (A)** 3.4

**Power (W)** 530

**Refrigerant mass (g)** 90

**Finish ext/int** 304 S/S & Alu

**Number of sections** 2

**Section configuration** LeftHinge,RightHinge

**System** Integral

<b>Height (mm)</b>	895	<b>Climate Class</b>	5
<b>Width (mm)</b>	870	<b>Energy grade</b>	G
<b>Depth (mm)</b>	745	<b>EEI</b>	114.64
<b>Gross volume (ltr)</b>	240	<b>AEC (kWh)</b>	2729
<b>Net volume (ltr)</b>	133.7	<b>Energy consumption (kWh/24hr)</b>	7.475
<b>Leg type</b>	Roller castors rear, levelling bolts front	<b>GWP</b>	3
<b>GN size</b>	1/1		
<b>Gross weight (kg)</b>	115		
<b>Net weight (kg)</b>	90.5		

## Footnotes

- For ventilation, ensure that 50mm clearance is allowed above and around the cabinet

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU  
+44 (0)1553 691122 | sales@foster-gamko.com | [www.fosterrefrigerator.com](http://www.fosterrefrigerator.com)

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.