



MILLENNIUM ST24

Ventilated Scoop Ice Cream Display

Product Features

- Great product visibility
- Flat glass top
- Accepts Napoli pans (not supplied)
- LED interior light with switch
- Digital controller and temperature display
- Front glass hinges forward if required
- Double glazed glass on sides
- Heated glass to help prevent condensation

Professional 24 scoop ventilated ice cream display with

The Millennium ST24 ice cream display cabinet is the epitome of luxury for discerning ice cream retailers. This 24 napoli pan display is designed to showcase your ice cream in the most impressive way possible. Contemporary flat glass that is heated to reduce minimise condensation, the display creates a stunning visual appeal, while the efficient, ventilated cooling system keeps your ice cream or gelato at the perfect serving temperature, ensuring that it remains fresh and delicious Plus, the rear features a pull-down night curtain to maintain cabinet temperature during slower periods and the front glass hinges forwards to make cleaning easier. If you're looking for a high-end scooping display cabinet that truly sets you apart, the Millennium ST24 is the ideal choice.

Serving Capacity 24 Napoli Pans (5 L) Storage capacity (under) No Under Storage Total Display Area m² 1.43 Temperature Range °C -20 to -14 Climate Class 7 Gross / Net Weight kg 478 / 412 Gross / Net Volume 1 1300 / 241 Design and Material White Interior Finish White Interior Finish Stainless steel Interior Light LED Cooling and Functions LED Type of Cooling Ventilated Type of Defrost Automatic, hot gas Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption KWh/24h 34 Annual Energy Consumption KWh/year 12410 Power 16 Amp Single Phase Commando Socket 10 Input Power V 2640 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimension (WxDxH)	Measures and Content		
Total Display Aream²1.43Temperature Range°C-20 to -14Climate Class7Gross / Net Weightkg478 / 412Gross / Net VolumeI1300 / 241Design and MaterialImage: Stainless steelExterior FinishWhiteInterior LightLEDCooling and FunctionsType of CoolingVentilatedType of CoolingVentilatedType of DefrostAutomatic, hot gasRefrigerantR290Refrigerant Chargeg2 x 148ThermometerPower and ConsumptionS5°C at 75% RHEnergy ClassDMax Ambient35°C at 75% RHEnergy ConsumptionkWh/24hPower16 Amp Single Phase Commando SocketInput PowerW2640Voltage / FrequencyVHz220-240/50Noise LeveldB(A)Dimension (WxDxH)mmExternal Dimension (WxDxH)mmParticit stream S	Serving Capacity		24 Napoli Pans (5 L)
Temperature Range°C-20 to -14Climate Class7Gross / Net Weightkg478 / 412Gross / Net VolumeI1300 / 241Design and MaterialExterior FinishWhiteInterior FinishStainless steelInterior LightLEDCooling and FunctionsVentilatedType of CoolingVentilatedType of CoolingVentilatedType of DefrostAutomatic, hot gasRefrigerantR290Refrigerant Chargeg2 x 148ThermometerYesPower and ConsumptionKWh/24hEnergy ClassDMax Ambient35°C at 75% RHEnergy ConsumptionkWh/yearInput Power16 Amp Single Phase Commando SocketInput PowerW2640Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)Dimensions530 x 1550 x 1620Power and Dimension (WxDxH)mmExternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mmPacked Dimension (WxDxH)mmPacked Dimension (WxDxH)mmPacked Dimension (WxDxH)mmState Son (State Son (Storage capacity (under)		No Under Storage
Climate Class7Gross / Net Weightkg478 / 412Gross / Net VolumeI1300 / 241Design and MaterialExterior FinishWhiteInterior FinishStainless steelInterior LightLEDCooling and FunctionsLEDType of CoolingVentilatedType of CoolingVentilatedType of DefrostAutomatic, hot gasRefrigerantR290Refrigerant Chargeg2 x 148ThermometerPower and ConsumptionYesEnergy ClassDMax Ambient35°C at 75% RHEnergy ConsumptionkWh/24hPower16 Amp Single Phase Commando SocketInput PowerW2640Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)58DimensionsInternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mmAutomation (WxDxH)mmAutomation (WxDxH)mmExternal Dimension (WxDxH)mmAutomation (WxDxH	Total Display Area	m²	1.43
Gross / Net Weightkg478 / 412Gross / Net VolumeI1300 / 241Design and MaterialI1300 / 241Exterior FinishWhiteInterior FinishStainless steelInterior LightLEDCooling and FunctionsVentilatedType of CoolingVentilatedType of DefrostAutomatic, hot gasRefrigerantR290Refrigerant Chargeg2 x 148ThermometerYesPower and ConsumptionStar 75% RHEnergy ClassDMax Ambient35°C at 75% RHEnergy ConsumptionkWh/24hPower16 Amp Single Phase Commando SocketInput PowerMB(A)Noise LeveldB(A)DimensionsSInternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mmAntonal Son (WxDxH)mmExternal Dimension (WxDxH)mm <t< td=""><td>Temperature Range</td><td>°C</td><td>-20 to -14</td></t<>	Temperature Range	°C	-20 to -14
Gross / Net VolumeI1300 / 241Design and MaterialI1300 / 241Exterior FinishWhiteInterior FinishStainless steelInterior LightLEDCooling and FunctionsVentilatedType of CoolingVentilatedType of DefrostAutomatic, hot gasRefrigerantR290Refrigerant Chargeg2 x 148ThermometerYesPower and ConsumptionDEnergy ClassDMax Ambient35°C at 75% RHEnergy ConsumptionkWh/24h34Annual Energy ConsumptionkWh/year12410Power16 Amp Single Phase Commando SocketInput PowerW2640Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)58DimensionsInternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mm2156 x 1054 x 1356Packed Dimension (WxDxH)mm2300 x 1550 x 1620	Climate Class		7
Design and MaterialExterior FinishWhiteInterior FinishStainless steelInterior LightLEDCooling and FunctionsLEDType of CoolingVentilatedType of DefrostAutomatic, hot gasRefrigerantR290Refrigerant ChargegPower and ConsumptionYesPower and ConsumptionS5°C at 75% RHEnergy ClassDMax Ambient35°C at 75% RHEnergy ConsumptionkWh/24hAnnual Energy ConsumptionkWh/yearInput Power16 Amp Single Phase Commando SocketInput PowerdB(A)State Level58Dimension (WxDxH)mmExternal Dimension (WxDxH)mmAutomation (WxDxH)mm <td>Gross / Net Weight</td> <td>kg</td> <td>478 / 412</td>	Gross / Net Weight	kg	478 / 412
Exterior FinishWhiteInterior FinishStainless steelInterior LightLEDCooling and FunctionsVentilatedType of CoolingVentilatedType of DefrostAutomatic, hot gasRefrigerantR290Refrigerant Chargeg2 x 148ThermometerYesPower and ConsumptionDEnergy ClassDMax Ambient35°C at 75% RHEnergy ConsumptionkWh/24hAnnual Energy ConsumptionkWh/yearPower16 Amp Single Phase Commando SocketInput PowerW2640Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)Dimension (WxDxH)mmExternal Dimension (WxDxH)mmPacked Dimension (WxDxH)mmAutomation (WxDxH)mmAutomation (WxDxH)mmAutomation (WxDxH)2300 x 1550 x 1620Automation (WxDxH)mmAutomation (WxDxH)MmAutomation (WxDxH)MmAutomation (WxDxH)MmAutomation (WxDxH)MmAutomation (WxDxH)MmAutomation (WxDxH)Automation (WxDxH)Automation (WxDxH)MmAutomation (WxDxH)MmAutomation (WxDxH)Automation (WxDxH)Automation (WxDxH)Automation (WxDxH)Automation (WxDxH)MmAutomation (WxDxH)Automation (WxDxH)Automation (WxDxH)MmAutomation (WxDxH)Autom	Gross / Net Volume	I	1300 / 241
Interior Finish Stainless steel Interior Finish LED Cooling and Functions Type of Cooling Ventilated Type of Defrost Automatic, hot gas Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption Energy Class D Max Ambient S5°C at 75% RH Energy Consumption kWh/24h 34 Annual Energy Consumption kWh/year 12410 Power 16 Amp Single Phase Commando Socket Input Power W 2640 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm 2156 x 1054 x 1356 Packed Dimension (WxDxH) mm 2156 x 1054 x 1356 Packed Dimension (WxDxH) mm	Design and Material		
Interior Light LED Cooling and Functions Type of Cooling Ventilated Type of Defrost Automatic, hot gas Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption Energy Class D Max Ambient S5°C at 75% RH Energy Consumption kWh/24h 34 Annual Energy Consumption kWh/24h 34 Annual Energy Consumption kWh/year 12410 Power 16 Amp Single Phase Commando Socket Input Power W 2640 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 2156 x 1054 x 1356 Packed Dimension (WxDxH) mm	Exterior Finish		White
Cooling and FunctionsType of CoolingVentilatedType of DefrostAutomatic, hot gasRefrigerantR290Refrigerant Chargeg2 x 148ThermometerYesPower and ConsumptionEnergy ClassDMax Ambient35°C at 75% RHEnergy ConsumptionkWh/24hAnnual Energy ConsumptionkWh/year16 Amp Single Phase Commando SocketInput Power16 Amp Single Phase Commando SocketInput PowerW220-240/50Noise LeveldB(A)58DimensionsInternal Dimension (WxDxH)mm2300 x 1550 x 1620Packed Dimension (WxDxH)mm2300 x 1550 x 1620	Interior Finish		Stainless steel
Type of CoolingVentilatedType of DefrostAutomatic, hot gasRefrigerantR290Refrigerant Chargeg2 x 148ThermometerYesPower and ConsumptionEnergy ClassDMax Ambient35°C at 75% RHEnergy ConsumptionkWh/24hAnnual Energy ConsumptionkWh/yearPower16 Amp Single Phase Commando SocketInput PowerW2640Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)DimensionsInternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mm2300 x 1550 x 1620Packed Dimension (WxDxH)mmExternal Dimension (WxDxH)mmTuber for the form2300 x 1550 x 1620	Interior Light		LED
Type of DefrostAutomatic, hot gasRefrigerantR290Refrigerant Chargeg2 x 148ThermometerYesPower and ConsumptionEnergy ClassDMax Ambient35°C at 75% RHEnergy ConsumptionkWh/24hAnnual Energy ConsumptionkWh/yearPower16 Amp Single Phase Commando SocketInput PowerW200 X/Hz220-240/50Noise LeveldB(A)58DimensionsmmExternal Dimension (WxDxH)mmPacked Dimension (WxDxH)mmPacked Dimension (WxDxH)mmXHS230 x 1550 x 1620	Cooling and Functions		
RefrigerantR290Refrigerant Chargeg2 x 148ThermometerYesPower and ConsumptionYesEnergy ClassDMax Ambient35°C at 75% RHEnergy ConsumptionkWh/24hAnnual Energy ConsumptionkWh/year16 Amp Single Phase Commando SocketInput Power16 Amp Single Phase Commando SocketInput PowerW2640Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)58DimensionsInternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mm2300 x 1550 x 1620Variation (WxDxH)mm	Type of Cooling		Ventilated
Refrigerant Chargeg2 x 148ThermometerYesPower and ConsumptionYesEnergy ClassDMax Ambient35°C at 75% RHEnergy ConsumptionkWh/24hAnnual Energy ConsumptionkWh/yearPower16 Amp Single Phase Commando SocketInput PowerWVoltage / FrequencyV/Hz220-240/50Noise LeveldB(A)DimensionsInternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mm2300 x 1550 x 1620Vation of the pace of t	Type of Defrost		Automatic, hot gas
ThermometerYesPower and ConsumptionEnergy ClassDMax Ambient35°C at 75% RHEnergy ConsumptionkWh/24hAnnual Energy ConsumptionkWh/yearPower16 Amp Single Phase Commando SocketInput PowerW2640Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)58DimensionsInternal Dimension (WxDxH)mm2156 x 1054 x 1356Packed Dimension (WxDxH)mm2300 x 1550 x 1620	Refrigerant		R290
Note of the second seco	Refrigerant Charge	g	2 x 148
Energy ClassDMax Ambient35°C at 75% RHEnergy ConsumptionkWh/24hAnnual Energy ConsumptionkWh/yearPower16 Amp Single Phase Commando SocketInput PowerWVoltage / FrequencyV/Hz220-240/50Noise LeveldB(A)58DimensionsInternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mm230 x 1550 x 1620	Thermometer		Yes
Max Ambient35°C at 75% RHEnergy ConsumptionkWh/24h34Annual Energy ConsumptionkWh/year12410Power16 Amp Single Phase Commando SocketInput PowerW2640Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)58DimensionsInternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mm2156 x 1054 x 1356Packed Dimension (WxDxH)mm2300 x 1550 x 1620	Power and Consumption		
Energy ConsumptionkWh/24h34Annual Energy ConsumptionkWh/year12410Power16 Amp Single Phase Commando SocketInput PowerW2640Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)58DimensionsInternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mm2156 x 1054 x 1356Packed Dimension (WxDxH)mm2300 x 1550 x 1620	Energy Class		D
Annual Energy ConsumptionkWh/year12410Power16 Amp Single Phase Commando SocketInput PowerW2640Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)58DimensionsInternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mm2156 x 1054 x 1356Packed Dimension (WxDxH)mm2300 x 1550 x 1620	Max Ambient		35°C at 75% RH
Power16 Amp Single Phase Commando SocketInput PowerW2640Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)58DimensionsInternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mm2156 x 1054 x 1356Packed Dimension (WxDxH)mm2300 x 1550 x 1620	Energy Consumption	kWh/24h	34
Input PowerW2640Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)58DimensionsInternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mm2156 x 1054 x 1356Packed Dimension (WxDxH)mm2300 x 1550 x 1620	Annual Energy Consumption	kWh/year	12410
Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)58DimensionsInternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mm2156 x 1054 x 1356Packed Dimension (WxDxH)mm2300 x 1550 x 1620	Power	16 Amp Single Phase Commando Socket	
Noise LeveldB(A)58DimensionsmmInternal Dimension (WxDxH)mmExternal Dimension (WxDxH)mm2156 x 1054 x 1356Packed Dimension (WxDxH)mm2300 x 1550 x 1620	Input Power	W	2640
Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 2156 x 1054 x 1356 Packed Dimension (WxDxH) mm 2300 x 1550 x 1620	Voltage / Frequency	V/Hz	220-240/50
Internal Dimension (WxDxH)mmExternal Dimension (WxDxH)mm2156 x 1054 x 1356Packed Dimension (WxDxH)mm2300 x 1550 x 1620	Noise Level	dB(A)	58
External Dimension (WxDxH) mm 2156 x 1054 x 1356 Packed Dimension (WxDxH) mm 2300 x 1550 x 1620	Dimensions		
Packed Dimension (WxDxH) mm 2300 x 1550 x 1620	Internal Dimension (WxDxH)	mm	
	External Dimension (WxDxH)	mm	2156 x 1054 x 1356
40ft Container Load pcs 10	Packed Dimension (WxDxH)	mm	2300 x 1550 x 1620
	40ft Container Load	pcs	10





Suitable for Napoli Pans (accessory) Heated front glass