



COMPACT GLASSWASHERS

Our research indicates that 94% of customers would be put off going to an outlet again if confronted with dirty glassware. Ecomax glasswashers make it quick, simple and cost effective to deliver a high quality finish, every time.

ECOMAX G402 VERSUS ECOMAX PLUS G403/S

RACKS PER HOUR



MAX GLASS CLEARANCE HEIGHT



CYCLE TIME (secs)



WATER CONSUMPTION per cycle



DOUBLE SKINNED CONSTRUCTION



Turn over for full machine specs.

SPECIFICATIONS

GENERAL

DIMENSIONS

Max Glass Clearance Height

Depth Door Open

Number of racks

Rack size

Max pints/plates per rack

Max racks p/h

New weight (kg)

Rinse booster pump

Built in detergent dispenser

Built in rinse aid dispenser

Double skinned construction

CONTROLS

Class A air gap

Thermostop control

Programme times. secs

Water consumption/cycle

Wash tank capacity

Wash tank heating

Rinse tank capacity

Drain pump

Wash pump rating

Wash pump flow rate

Rinse pump rating

WATER

Integral softener

Water pressure

Water temp

ELECTRIC

Voltage 3P

Voltage 1P

Total loading 3P

Total loading 1P

ECOMAX

G402

435mm(w)

530mm(d)

700mm(h)

300mm

866mm

1 x 4 division glass rack

385 x 385mm

16

40

44

NO

YES

YES

DOOR

ELECTRONIC

NO

YES

90 – 120

2.5L

11L

2.0kW

4.9L

YES

0.25kW

150L/min

0.25kW

NO

2 – 6 BAR

N/A

400/50/3

230/50/1

3 x 16A/5.9kW

13A/2.2kW (Factory setting)

20A/4kW

ECOMAX PLUS

G403/S

460mm(w)

590mm(d)

700mm(h)

315mm

943mm

1 x 4 division glass rack

400 x 400mm

16

40

50

YES

YES

YES

FULL

ELECTRONIC

YES

YES

90 – 180

2.5L

8L

0.8kW

4L

YES

0.6kW

200L/min

0.1kW

YES

0.8 – 6 BAR

MAX 60°C

400/50/3

230/50/1

3 x 16A/5.4kW

13A/2.7kW(Factory setting)

20A/4.0kW



ECOMAX G402



ECOMAX PLUS G403/S

Technical details may be subject to change at any time without prior notice.

HOBART INDEPENDENT

Southgate Way, Orton Southgate,
Peterborough, PE2 6GN

0870 168 8881

or visit www.hobartindependent.co.uk