



GRAM GASTRO K 2207 CSG A DL/DL/DL/DR L2

Product series: Gastro

Item number: 952200021

The GRAM GASTRO K 2207 CSG A DL/DL/DL/DR L2 is a with a net internal volume of 384 Ltr.

GRAM Gastro 07 is a series of 1/1 GN workstations, equipped with customizable sections. Furthermore, the highly modular refrigerated counter offers an abundance of practical configuration possibilities.



Temperature Control

Thanks to the Gram air distribution system, temperatures inside the counters always maintain a uniform and correct level.

This includes rapid temperature recovery after every door opening.

Modularity & Scalability

With GRAM GASTRO 07 counters you can put together your individual workplace. Choose your combination of worktop, doors, and drawers, legs / castors/electric elevation, temperature ranges and accessories.

Easy Maintenance

A compact slide-out refrigeration unit for easy maintenance and service access. Removable and easy to clean condenser filters and gaskets.

Allergy-Proof

Counters are made from nickel-free stainless steel.

Ergonomic and practical design

Anti-tilt shelves and drawers with pull-out stop.

Extra-long telescopic rails on drawers - GN trays can be lifted in and out without tilting.

High Standard in Hygiene

The counter almost entirely consists of smooth surfaces – the perfect design for easy, quick and thorough cleaning.

'Drip Nose' edges on worktops to prevent the ingress of water.

Worktops with splashbacks to protect your counter from spillage.

Removable drawer and door gaskets for easy cleaning.

Pan-shaped inside base with rounded corners to catches fluid.

SPECIFICATIONS

Temperature range	+2/+12°C	Energy consumption (kWh/Year)	559
Volume, gross (ltr.)	668	Energy Efficiency Class (ISO 22041-2019)	A
Net usable volume (ltr.)	384	Energy Efficiency Index EEI	20.18
Exterior	Stainless	Sound level dB(A)	43.4
Interior	Stainless	Climate class	5
Dimensions W x D x H (mm)	2163 x 700 x 885/950	Legs / Castors	H = 135/200 mm (L2)
Weight, packed (kg)	221	Refrigerant (kg)	0.097
Insulation (mm)	50 mm (cyclopentane)	CO2 equivalent (kg)	0.291
Refrigerant	R290	GN or Shelf size	1/1 GN
GWP	3	Number of shelves	8
Ref. capacity at -10°C (Watt)	406	Equipped with	Stainless steel solid top, 4 door sections each with 2 stainless shelves
Connection	230V, 50 Hz	Door Type	Solid Door
Connection load (Watt)	190		