


MP 450 FW Ultra



EasyPlug

METAL
GEARBOX**A** SALES DESCRIPTION

Intended for Institutional and commercial caterers. Intensive use.

Whisk attachment for processing mashed potatoes, pan cakes, whipped cream...

B TECHNICAL DESCRIPTION

MP 450 FW Ultra Immersion Blender. 240V/50-60/1. Power 500 Watts ; Variable speed from 250 to 1500 rpm. Metal gear box even more resistant to support heavy strenghts. "EasyPlug" system featuring detachable power cord.

C TECHNICAL CHARACTERISTICS

Effective output	500 W
Electrical data	240V/50-60/1 2.1 A – plug supplied
Variable speed	250 - 1,500 rpm
Recyclability	95%
Net weight	6.1 kg
Reference	34881L

STANDARDS

EN 12100-1 & 2-2004, EN 60204-1-2006, EN 12853, EN 60529-2000 : IP55 & IP34

**D**

Pan capacity

up to 100 litres

E CHARACTERISTICS AND BENEFITS**MOTOR UNIT**

- Power 500 W
- Stainless-steel motor unit with air vents in the top section only to ensure watertightness
- Lug on motor housing serves as a rest and pivot on the pan rim for greater user comfort
- Variable speed: 250 - 1,500 rpm
- Self-regulating speed system
- New patented "EasyPlug" system making it easier to replace the power cord during after-sales servicing
- Cord winding system for tidy storage and optimum lifespan

WHISK

- Whisk attachment equipped with metal gear box even more resistant when processing pan cakes or fresh mashed potatoes.
- Fast coupling of the whisks on the gear box and the gear box on the motor base for easy assembling and dismantling.

STANDARD ATTACHMENTS

- Wall-mounted immersion blender holder
- Tool for fixing and detaching the blades

MP 450 FW Ultra



DRAWINGS & DIMENSIONS

230 V / 50 Hz / 1 ph – power cord and plug supplied

