



# GRAM GASTRO K 1407 CSG A 2D/3D L2

Product series: Gastro

Item number: 951400503

The GRAM GASTRO K 1407 CSG A 2D/3D L2 is a with a net internal volume of 154 Ltr.

GRAM Gastro 07 is a series of 1/1 GN workstations, equipped with customizable sections. Furthermore, the highly modular refrigerated counter offers an abundance of practical configuration possibilities.

#### Temperature Control

Thanks to the Gram air distribution system, temperatures inside the counters always maintain a uniform and correct level.

This includes rapid temperature recovery after every door opening.

#### Modularity & Scalability

With GRAM GASTRO 07 counters you can put together your individual workplace. Choose your combination of worktop, doors, and drawers, legs / castors/electric elevation, temperature ranges and accessories.

#### Easy Maintenance

A compact slide-out refrigeration unit for easy maintenance and service access. Removable and easy to clean condenser filters and gaskets.

#### High Standard in Hygiene

- The counter almost entirely consists of smooth surfaces – the perfect design for easy, quick and thorough cleaning.
- 'Drip Nose' edges on worktops to prevent the ingress of water.
- Worktops with splashbacks to protect your counter from spillage.
- Removable drawer and door gaskets for easy cleaning.
- Pan-shaped inside base with rounded corners to catches fluid.

#### Allergy-Proof

Counters are made from nickel-free stainless steel.

#### Ergonomic and practical design

- Anti-tilt shelves and drawers with pull-out stop.
- Extra-long telescopic rails on drawers - GN trays can be lifted in and out without tilting.

## SPECIFICATIONS

Temperature range	+2/+12°C	Connection load (Watt)	190
Volume, gross (ltr.)	345	Energy consumption (kWh/Year)	551
Net usable volume (ltr.)	154	Energy Efficiency Class (ISO 22041-2019)	B
Exterior	Stainless	Energy Efficiency Index EEI	25.22
Interior	Stainless	Climate class	5
Dimensions W x D x H (mm)	1289 x 700 x 885/950	Legs / Castors	H = 135/200 mm (L2)
Weight, packed (kg)	140	Refrigerant (kg)	0.097
Insulation (mm)	50 mm (cyclopentane)	CO2 equivalent (kg)	0.291
Refrigerant	R290	GN or Shelf size	1/1 GN
GWP	3	Equipped with	Stainless steel solid top. One drawer sections with 2 x 1/2 drawers and one drawer section with 3 x 1/3 drawers
Ref. capacity at -10°C (Watt)	406	Door Type	Solid Door
Connection	230V, 50 Hz		