

MP 450 XL FW Ultra



EasyPlug

D

Pan capacity

up to 100 litres

A

SALES DESCRIPTION

Intended for institutional and commercial caterers. Intensive use.

Mixing Tool for potato flakes, dry soups, deshydrated base for sauce, spices + sauces, deshydrated mixes for pastry.

B

TECHNICAL DESCRIPTION

MP 450 XL FW Ultra Immersion Blender. 240V/50-60/1. Power 500 Watts ; Variable speed from 250 to 1500 rpm. Metal gear box resistant to support heavy strenghts. "EasyPlug" system featuring detachable power cord.

C

TECHNICAL CHARACTERISTICS

Effective output	500 W
Electrical data	240V/50-60/1 2.3 A – plug supplied
Variable speed	150 - 510 rpm
Recyclability	95%
Net weight	5.3 Kg
Reference	34281L

STANDARDS

EN 12100-1 & 2-2004, EN 60204-1-2006, EN 12853, EN 60529-2000 : IP55 & IP34



E

CHARACTERISTICS AND BENEFITS

MOTOR UNIT

- Power 500 W
- Stainless-steel motor unit with air vents in the top section only to ensure watertightness
- Lug on motor housing serves as a rest and pivot on the pan rim for greater user comfort
- Variable speed: 150 - 510 rpm
- Self-regulating speed system
- New patented "EasyPlug" system making it easier to replace the power cord during after-sales servicing
- Cord winding system for tidy storage and optimum lifespan

MIXING TOOL ATTACHMENT

- Boite fouet métallique pour une grande robustesse.

STANDARD ATTACHMENTS

- Wall-mounted immersion blender holder

MP 450 XL FW Ultra

G

DRAWINGS & DIMENSIONS

230 V / 50 Hz / 1 ph – power cord and plug supplied

