Multideck With Shutter

MCX Range





Description

MCX Range is an open front, stainless steel multideck, ideal for grab and go and impulse purchases. The unit benefits from a rigid lockable security shutter to prevent access to product when food is not being served and lockable castors. The cabinet is the perfect solution for a range of sites such as cafeterias, hotels, colleges, and university canteens. It fulfils the need for multidecks during service while also prioritising product security during non-service periods.

Product Features	Technical Specification	IS		
Rigid lockable shutter	Temperature Range (°C)	-1 to +5		
Ventilated cooling	Refrigerant	R290		
Adjustable shelves	Type of Defrost	Automatic		
 Fully automatic Castors with brake 	Exterior Finish	Stainless steel		
LED interior light with switch	Interior Finish	Stainless steel		
Digital controller and temperature	Power	13 Amp		
display	Max Ambient	25°C 60% RH		
	Climate Class	3		
Ext. Dimension Int. Dimension	n Net Weight Energy Cons. Inp	out Power Display Area No. of Energy		

	Ext. Dimension (WxDxH) (mm)	lnt. Dimension (WxDxH) (mm)	Net Weight (kg)	Energy Cons. (kWh/year)	lnput Power (W)	Display Area (m²)	No. of Shelves	Energy Class
MCX90M	868 x 630 x 1920	806 x 436 x 1250	160	3865	670	0,89	4	EG
MCX130M	1312 x 630 x 1920	1250 x 436 x 1250	230	6449	1080	1,46	4	F A
MCX150M	1512 x 630 x 1920	1450 x 436 x 1250	255	6770	1210	1,72	4	F A
MCX200M	1937 x 630 x 1920	1875 x 436 x 1250	320	7455	1490	2,26	4	E A



Multideck With Shutter MCX Range

