



SF224

Juice Dispensers

Product Features

- Paddle system agitation
- Fully automatic
- Suitable for milk and fruit juice containing pulp
- Easy Dispense
- Easy Clean (includes fully stainless steel tap system)
- Waterproof Switches
- Easily Removable Drip Tray
- Not suitable for milk, slush or ice cream smoothies

Measures and Content		
Temperature Range	°C	+2 to +10
Climate Class		3
Gross / Net Weight	kg	24 / 34
Gross / Net Volume	I	24 /
Design and Material		
Door Number & Type		
Shelves Number & Type		
Exterior Finish		Stainless steel
Cooling and Functions		
Type of Defrost		Off Cycle
Refrigerant		R290
Thermometer		Yes
Power and Consumption		
Power and Consumption Energy Consumption	kWh/24h	1.75
	kWh/24h kWh/year	1.75
Energy Consumption		
Energy Consumption Annual Energy Consumption		639
Energy Consumption Annual Energy Consumption Power		639 13 Amp
Energy Consumption Annual Energy Consumption Power Max Ambient	kWh/year	639 13 Amp 25°C at 60% RH
Energy Consumption Annual Energy Consumption Power Max Ambient Input Power	kWh/year W	639 13 Amp 25°C at 60% RH 160
Energy Consumption Annual Energy Consumption Power Max Ambient Input Power Voltage / Frequency	kWh/year W V/Hz	639 13 Amp 25°C at 60% RH 160 220-240/50
Energy Consumption Annual Energy Consumption Power Max Ambient Input Power Voltage / Frequency Noise Level	kWh/year W V/Hz	639 13 Amp 25°C at 60% RH 160 220-240/50
Energy Consumption Annual Energy Consumption Power Max Ambient Input Power Voltage / Frequency Noise Level Dimensions	kWh/year W V/Hz dB(A)	639 13 Amp 25°C at 60% RH 160 220-240/50
Energy Consumption Annual Energy Consumption Power Max Ambient Input Power Voltage / Frequency Noise Level Dimensions Internal Dimension (WxDxH)	kWh/year W V/Hz dB(A)	639 13 Amp 25°C at 60% RH 160 220-240/50 54
Energy Consumption Annual Energy Consumption Power Max Ambient Input Power Voltage / Frequency Noise Level Dimensions Internal Dimension (WxDxH) External Dimension (WxDxH)	kWh/year W V/Hz dB(A) mm mm	639 13 Amp 25°C at 60% RH 160 220-240/50 54 380 × 385 × 620

