



SILVERLINK 600

Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down. The hard-wearing 12 mm thick steel plate provides even heat distribution and excellent heat retention, while the griddle is thermostatically controlled to give accurate temperatures during the cooking process for consistent results. The griddle, perfect for cafes, pubs and restaurants, is designed to plug in and play, so you'll be cooking mouthwatering dishes in no time.

A/A FILE NUMBER:

PRODUCT OPTIONS AND ACCESSORIES

- CC3 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 300 mm
- CN3 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 300 mm
- SLS3 Lincat Silverlink 600 Free-standing Floor Stand - for units W 300 mm
- HC3 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 300 mm - 0.25 kW
- HCL3 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 300 mm - 0.25 kW

PRODUCT FEATURES

- Hard wearing 12 mm thick machined steel plate providing even heat distribution and excellent heat retention
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Removable front drainer drawer which also makes for easy cleaning. Ideal for busy establishments
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up
- Plug and play for an easy installation

ITEM NUMBER:

WEIGHTS & DIMENSIONS

Width	300 mil
Depth	600 mil
Height	330 mil
Weight	22 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	40 cm
Ship Height	49.5 cm
Ship Weight	24.2 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	8.7	Electrical Connection Type	Cord and Plug
Electrical Voltage	230 volts	Electrical Plug Type	UK 3-Pin Plug
Electrical Watts	2000	Number of Electrical Plugs	1
Electrical Phase	Single	Dedicated Circuit Required	No
Kilowatts	2 kW	Energy Saving	No

ADDITIONAL SPECIFICATIONS

Control Type	Rotary Control Knob	Number of Heating Zones	2
Cooking Area Plate Depth	405 mm	Plate Shape	Rectangle
Cooking Area Plate Width	262 mm	Plate Thickness	12 mm
Cooking Plate Finish Material Type	Polished Steel	Temperature Maximum	250 °C
Legs or Casters	Not Applicable	Temperature Minimum	50 °C
Lower Platen Surface Type (multi-select)	Smooth	Thermostat Element Location	Under Plate Mount
Number Of Controls	2		

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

