

COOL PRODUCTS WORLDWIDE



## **MCX130M**

Multideck with shutter

## **Product Features**

- Ideal for impulse buys and promotions
- Lockable security shutter
- Ventilated cooling
- · Adjustable shelves
- Fully automatic
- Castors with brake
- LED interior light with switch
- Digital controller and temperature display
- Ticket strip included

Stainless steel mutidecks with lockable security shutter

The TEFCOLD MCX Range is an open front stainless steel multideck, ideal for grab and go and impulse purchases. It can be set to temperature suitable for drink, dairy or fresh meat to suit your requirements. The MCX also benefits from a rigid lockable security shutter to prevent access to product when food is not being served, it is also supplied on lockable castors to allow movement of the cabinet. This allows the unit to be more versatile as to where it can be utilised to maximise sales. The MCX Range is is the perfect solution for a wide range of establishments such as cafeterias, hotels, schools, colleges, and university canteens. It caters to the need for a refrigerated multideck during service while also prioritising product security during non-service periods. This feature becomes especially valuable in environments where customers, staff, or students may still have access to the unit.

| Measures and Content       |          |                   |
|----------------------------|----------|-------------------|
| Total Display Area         | m²       | 1.46              |
| Temperature Range          | °C       | -1 to +5          |
| Climate Class              |          | 3                 |
| Gross / Net Weight         | kg       | 310 / 230         |
| Gross / Net Volume         | 1        | 680 / 580         |
| Design and Material        |          |                   |
| Shelves Number & Type      |          | 4 adjustable      |
| Shelf Color                |          | Stainless steel   |
| Castors                    |          | Castors           |
| Exterior Finish            |          | SS304             |
| Interior Finish            |          | SS304             |
| Interior Light             |          | LED as option     |
| Cooling and Functions      |          |                   |
| Type of Controller         |          | Electronic        |
| Type of Cooling            |          | Ventilated        |
| Type of Defrost            |          | Automatic         |
| Refrigerant                |          | R290              |
| Refrigerant Charge         | g        | 2 x 140           |
| Thermometer                |          | Yes               |
| Power and Consumption      |          |                   |
| Energy Class               |          | F                 |
| Energy Consumption         | kWh/24h  | 17.67             |
| Annual Energy Consumption  | kWh/year | 6449              |
| Power                      |          | 13 Amp            |
| Max Ambient                |          | 25°C 60% RH       |
| Input Power                | W        | 1080              |
| Voltage / Frequency        | V/Hz     | 220-240/50        |
| Noise Level                | dB(A)    | 61                |
| Dimensions                 |          |                   |
| Internal Dimension (WxDxH) | mm       | 1250 x 436 x 1250 |
| External Dimension (WxDxH) | mm       | 1312 x 740 x 1994 |
| Packed Dimension (WxDxH)   | mm       | 1400 x 790 x 2150 |
| 40ft Container Load        | pcs      | 22                |





Security shutter with lock

Strong castors