



**Green** Gastronorm Refrigerator Counters  
**SPI-7-135-20 / SPI-7-180-30 / SPI-7-225-40**



2 YEARS  
WARRANTY



2-3 DAY  
DELIVERY



UK SERVICE  
SUPPORT



MADE IN  
THE EU



**Specifications**

Model	Doors	Upstand	Capacity Gross / Nett		Temperature	Energy Usage	Dimensions (mm) Width / Depth / Height			Energy Rating	Refrigerant
<b>SPI-7-135-20</b>	2	Yes	290 ltrs	143 ltrs	-2°C to +8°C	2.0 kW/hr	1342	700	850	B	R600a
<b>SPI-7-135-20-SP</b>	2	No	290 ltrs	143 ltrs	-2°C to +8°C	2.0 kW/hr	1342	700	850	B	R600a
<b>SPI-7-180-30</b>	3	Yes	452 ltrs	214 ltrs	-2°C to +8°C	2.6 kW/hr	1792	700	850	C	R600a
<b>SPI-7-180-30-SP</b>	3	No	452 ltrs	214 ltrs	-2°C to +8°C	2.6 kW/hr	1792	700	850	C	R600a
<b>SPI-7-225-40</b>	4	Yes	615 ltrs	285 ltrs	-2°C to +8°C	3.0 kW/hr	2242	700	850	C	R600a
<b>SPI-7-225-40-SP</b>	4	No	615 ltrs	285 ltrs	-2°C to +8°C	3.0 kW/hr	2242	700	850	C	R600a

**Key Features**

Power supply: 13 amp plug

Castors fitted as standard

Heavy-duty forced air system

Stainless Steel interior and exterior

Automatic defrost

Intelligent air-circulation system

Drawer options available

100mm upstand available at no extra cost

## Green Gastronorm Refrigerator Counters SPI-7-135-20 / SPI-7-180-30 / SPI-7-225-40



2 YEARS  
WARRANTY



2-3 DAY  
DELIVERY



UK SERVICE  
SUPPORT



MADE IN  
THE EU

### Efficiency

- "Ventilation Gill" on the front panel keeping the cooling unit system ventilated and running more efficiently.
- Forced draft evaporator with anti-corrosion cover.
- Intelligent Air Circulation system ensures perfect temperature consistency with its innovative airflow design.
- 50 mm thickness, CFC-free, high-density (40 kg/m<sup>3</sup>) polyurethane insulation, injected under high pressure

### Features

- Fitted with foot pedal and castors. Legs available as an option. Height-adjustable legs available as an option (125mm - 200mm).
- Removable guiding rails enable more convenient cleaning operations without any additional tools. Placing and adjusting the wire grids at the desired height is possible without using extra rails. Epoxy-coated wire grids, to improve protection, allow storage of different packaging types and have a maximum loading capacity of up to 40 kg.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
- Heavy-duty stainless steel 50mm working top with 100mm high splash-back, preventing spillage behind the counter.
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and closes automatically at less than 90°. Door hinges are also reversible allowing the counter to be adapted on-site.
- Control panel and engine ventilation with pivoting front opening.
- Intuitive digital control allows temperature parameters to be adjusted easily and quickly.
- Luminous start-stop light button.
- Automatic evaporation of defrost water. Hot gas coming from the compressor is used to automatically evaporate defrost water, instead of by means of heating elements, achieving even less energy consumption and reducing in half defrost time.
- Equipped with 1 grid GN 1/1 per each door.
- Rounded edge interiors, easier cleaning operations to reduce potential dirt traps.

### Contact

**Website:** [www.sterlingpro.co.uk](http://www.sterlingpro.co.uk) / **Phone:** 01264 560190 / **Email:** [sales@sterlingpro.co.uk](mailto:sales@sterlingpro.co.uk)