



## PHGBP80/N - Lincat Phoenix Free-standing Gas Bratt Pan - 81 Litres - 20.0 kW

Solve cooking needs even at high temperatures. Tilting bratt pan designed to meet the daily needs of small and medium sized restaurants, the catering sector and centralised cooking centres.

- ✓ Large 80 litre capacity
- ✓ Perfect for bulk cooking in a variety of methods - allows users to braise, shallow fry or boil a variety of food products in large quantities
- ✓ Temperature control flexible from 45°C to 295°C - maximum flexibility to meet different cooking needs
- ✓ Handwheel controlled manual tilting for a smooth tilt
- ✓ Large pouring spout for easy emptying of the pan, reducing mess
- ✓ High thermal efficiency stainless steel tubular burners
- ✓ AISI 304 grade stainless steel for uniform heat distribution, perfect for high temperature cooking
- ✓ Robust 12mm thick base
- ✓ Easy clean stainless steel design

### Specifications

#### Summary

<b>Brand</b>	Lincat
<b>Range</b>	Phoenix
<b>Power Type</b>	Gas
<b>Gas Type</b>	Natural (LPG jets supplied for onsite conversion)
<b>Unit Type</b>	Free-standing
<b>Available in UK Only</b>	No
<b>UK Warranty</b>	2 Years Parts and Labour Warranty
<b>Export Warranty</b>	Contact your local dealer
<b>GTIN</b>	5056105121930

#### Power and Performance

<b>BTU per Hour</b>	68,250
<b>Total Power kW</b>	20
<b>Temperature Range °C</b>	45-295
<b>IP Rating</b>	IPX4
<b>Temperature Control</b>	Mechanical

#### Capacity

<b>Capacity Litres</b>	81
------------------------	----

#### Weights and Dimensions

<b>Unit Height (External) mm</b>	970
<b>Unit Width (External) mm</b>	800
<b>Unit Depth (External) mm</b>	900
<b>Height (Internal) mm</b>	200
<b>Width (Internal) mm</b>	698
<b>Depth (Internal) mm</b>	564
<b>Net Weight Kg</b>	140

Supply Connections		Shipping	
Requires Installation	Yes	Packed Weight Kg	180
Requires Electrical Supply	Yes	Packed Height cm	115
Requires Hardwiring	No	Packed Width cm	87
Gas Connection BSP	3/4"	Packed Depth cm	107
Gas Consumption at full rate Natural m <sup>3</sup> per Hour	2.12		
Gas Consumption at full rate Propane m <sup>3</sup> per Hour	1.58		
Gas Pressure Natural mbar	20		
Gas Pressure Propane mbar	28-30/37		
Total heat input at full rate Natural kW	20		
Total heat input at full rate Propane kW	20		
Total heat input at full rate Natural BTU per hour	68,250		
Total heat input at full rate Propane BTU per hour	68,250		
Water Connection Pressure Bar	0.5-3		
Water Connection	1/2"		



**Lincat Limited**

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

**Company No:** 2175448

A member company of



**Customer Care**

**Tel:** +44 1522 875500  
**Email:** care@lincat.co.uk

**Export Customers**

**Tel:** +44 1522 875536  
**Email:** export@lincat.co.uk

**Opening Hours**

**Monday – Friday:**  
8.30am – 5pm