


BTD130BKGDV2



NEW UPRIGHT SLIDING GLASS DOOR BLACK/STAINLESS STEEL MULTI-DECK

Description

The new and improved BTDRange from Blizzards is here and it comes with a fresh new look and thanks to some improved features is more cost efficient than ever with its new and improved energy rating! Fronted with double glazed glass doors the GD closed version of the BTDRange line up is perfect for venues looking to offer easy access to their goods while still being energy conscious and although not exactly being the lightest unit in the world is easily manoeuvrable thanks to its integrated castor feet. Offering a premium look without breaking the bank and thanks to its 4 included, adjustable shelves you will never be short of merchandising space whether you're looking to display drinks upright or tilt the shelves for a better viewing angle of your freshly prepared sandwiches!

3
YEAR
WARRANTY

NEW
ARRIVAL

CASTORS
INCLUDED

LED
LIGHTING

CLIMATE
CLASS 4

Features

- Double glazed sliding glass doors
- Double glazed glass side panels
- 4 Adjustable heavy duty shelves
- Detachable plastic pricing strips
- Internal LED illumination
- Digital temperature controller
- Independent power/lighting switches
- Castor-feet supplied as standard
- Front vented condenser unit

MODEL	FINISH	SHELVES	GROSS CAPACITY	REFRIGERANT	TEMPERATURE RANGE	DIMENSIONS (mm)	ENERGY RATING	POWER USAGE	KWH/ANNUM	POWER	WEIGHT (kg)
BTD100SSGDV2	Stainless Steel	4	560L	R290	0°C / +5°C	H2000 x W1000 x D800	A+ G C	670W	3486	13amp	280
BTD100BKGDV2	Black	4	560L	R290	0°C / +5°C	H2000 x W1000 x D800	A+ G C	670W	3486	13amp	280
BTD130SSGDV2	Stainless Steel	4	750L	R290	0°C / +5°C	H2000 x W1315 x D800	A+ G C	690W	4194	13amp	339
BTD130BKGDV2	Black	4	750L	R290	0°C / +5°C	H2000 x W1315 x D800	A+ G C	690W	4194	13amp	339
BTD150SSGDV2	Stainless Steel	4	873L	R290	0°C / +5°C	H2000 x W1520 x D800	A+ G C	850W	4719	13amp	390
BTD150BKGDV2	Black	4	873L	R290	0°C / +5°C	H2000 x W1520 x D800	A+ G C	850W	4719	13amp	390
BTD200SSGDV2	Stainless Steel	4	1125L	R290	0°C / +5°C	H2000 x W1940 x D800	A+ G C	990W	5504	13amp	499
BTD200BKGDV2	Black	4	1125L	R290	0°C / +5°C	H2000 x W1940 x D800	A+ G C	990W	5504	13amp	499
BTD250SSGDV2	Stainless Steel	4	1500L	R290	0°C / +5°C	H2000 x W2565 x D800	A+ G C	1140W	6552	13amp	580