

GRAM GASTRO K 2207 CSG A 2D/2D/3D/3D L2

Product series: Gastro Item number: 952200511

The GRAM GRAM GASTRO K 2207 CSG A 2D/2D/3D/3D L2 $\,$ is a with a net internal volume of 308 Ltr.

GRAM Gastro 07 is a series of 1/1 GN workstations, equipped with customizable sections. Furthermore, the highly modular refrigerated counter offers an abundance of practical configuration possibilities.



Temperature Control

Thanks to the Gram air distribution system, temperatures inside the counters always maintain a uniform and correct level.

This includes rapid temperature recovery after every door opening.

Modularity & Scalability

With GRAM GASTRO 07 counters you can put together your individual workplace. Choose your combination of worktop, doors, and drawers, legs /castors/electric elevation, temperature ranges and accessories.

Easy Maintenance

A compact slide-out refrigeration unit for easy maintenance and service access. Removable and easy to clean condenser filters and gaskets.

High Standard in Hygiene

- The counter almost entirely consists of smooth surfaces the perfect design for easy, quick and thorough cleaning.
- 'Drip Nose' edges on worktops to prevent the ingress of water.
- Worktops with splashbacks to protect your counter from spillage.
- Removable drawer and door gaskets for easy cleaning.
- Pan-shaped inside base with rounded corners to catches fluid.

Allergy-Proof

Counters are made from nickel-free stainless steel.

Ergonomic and practical design

- Anti-tilt shelves and drawers with pull-out stop.
- Extra-long telescopic rails on drawers GN trays can be lifted in and out without tilting.

SPECIFICATIONS

+2/+12°C	Connection	230V, 50 Hz
668	Connection load (Watt)	190
308	Energy consumption (kWh/Year)	652
Stainless	Energy Efficiency Class (ISO 22041-2019)	В
Stainless	Energy Efficiency Index EEI	25.28
2163 x 719 x 885/950	Legs / Castors	H = 135/200 mm (L2)
221	Refrigerant (kg)	0.097
50 mm (cyclopentane)	CO2 equivalent (kg)	0.291
R290	GN or Shelf size	1/1 GN
3	Equipped with	Stainless steel solid top, 2 drawer sections
406		each with 2 x 1/2 drawers and 2 drawer sections each with 3 x 1/3 drawers.
	Door Type	Solid Door
	668 308 Stainless Stainless 2163 x 719 x 885/950 221 50 mm (cyclopentane) R290 3	Connection load (Watt) 308 Energy consumption (kWh/Year) Stainless Energy Efficiency Class (ISO 22041-2019) Stainless Energy Efficiency Index EEI 2163 x 719 x 885/950 Legs / Castors 221 Refrigerant (kg) 50 mm (cyclopentane) CO2 equivalent (kg) R290 GN or Shelf size Equipped with