

COUNTERTOP CONVECTION OVEN

E711



E711

DESCRIPTION

Versatile, compact countertop, 1/1 gastronorm compatible fan-assisted convection oven. Ideal to be positioned upon a worktop or stand. Supplied with 13A plug, ready to plug in and use.

Easy to clean stainless steel exterior with simple controls to offer precise temperature control and specific timing. Temperature range is 50° - 240°C.

Oven chamber features integral light and multi-position runners. Six shelf positions provided with two shelf cooking. Shelf spacing is 65mm between runners. Three shelves supplied.

Designed for commercial use in a wide variety of locations such as pubs/restaurants, hotels and retail. The oven can be utilised anywhere there is a 13A socket.

FEATURES and BENEFITS

- Countertop model
 - Ideal for kitchens where space is limited
- Superior heat up and temperature recovery
 - Increased efficiency
- Gastronorm 1/1 compatible oven with 65mm spacing
 - Industry standard trays and shelves
- Enamelled oven linings are simple to clean
 - Easy to remove
- Simple plug in – no hard wiring required
 - 2.5 metre lead supplied, ready to use after unpacking

VENTILATION

Adequate ventilation, whether natural or mechanical, must be provided to supply sufficient fresh air. Recommendations for ventilation of appliances are given in BS5440:2 and HVCA specification DW/172.

For multiple installations, requirements for individual appliances should be added together. Installation of any such system must be completed in accordance with local and/or national regulations that apply at time of commissioning

OPTIONAL ACCESSORIES

- Oven shelf (*additional*)

SITING

Suitable for installation upon any flat horizontal surface.

Sufficient clearance should be left around oven to allow 180° rotation for maintenance purposes.








COUNTERTOP CONVECTION OVEN

E711

MODEL DIMENSIONS (in mm)



Electrical connection is lead with plug for immediate use.

SPECIFICATION DETAILS

E711

Shelf positions	6
Oven internal dimensions (mm)	546 (w) x 370 (d) x 405 (h)
Shelf size	1/1 gastronorm compatible (3 supplied)
Total rating (kW)	2.65
Electrical supply voltage	230V N~
Amps per phase (A)	L1 - 11.5
Weight (kg)	48
Packed weight (kg)	59