



Product Code: EP700F 10-232

EcoPro G2 600 Litre Upright Fish Cabinet



Features & Benefits

- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet
- This model optimises fish storage conditions with the cooling system designed to prevent surface drying of the fish.

External Finish

304 s/s	Standard
304 S/S back for island sitting	Option

Base Fittings

Castors 80mm	Standard
---------------------	----------

Electrical, Service & Ecodesign Data

230/50/1	Standard
220/60/1 Electrical Supply	Option
Fuse Required	13

Internal Finish

304 s/s	Standard
----------------	----------

Doors

Solid	Standard
--------------	----------

Left Hand Hinged Door	Option
------------------------------	--------

Product Extras

Helicoil Mains Lead	Option
----------------------------	--------

Shelving

Additional S/S Trayslides	Option
----------------------------------	--------

Additional GN2/1 Shelf	Option
-------------------------------	--------

Refrigeration

R290 - Energy Efficient	Standard
--------------------------------	----------

Less Condensing Unit	Option
-----------------------------	--------

Specification

Dimensions (Width)	700
Dimensions (Height)	2080
Dimensions (Depth)	820
Weight (Unpacked, kg)	121
Weight (Packed, kg)	132.6
Gross Volume	600
Noise DbA @ 1M	TBC

Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet



Energy



Quality



Value



Design



Hygiene



After Care