

JADE SLIMLINE COUNTER TECHNICAL DATASHEET

JSC2 JADE TWO DOOR SLIMLINE COUNTER



JSC3 JADE THREE DOOR SLIMLINE COUNTER



JSC2

Dimensions (mm)	External	Internal
Width	1400	870
Depth	500	385
Height	857	600
Door Opening		390
Capacity		cu.ft/ltrs
Capacity cu.ft/ltrs		8.6/244

JSC3

Dimensions (mm)	External	Internal
Width	1880	1350
Depth	500	385
Height	857	600
Door Opening		390
Capacity		cu.ft/ltrs
Capacity cu.ft/ltrs		13.2/374

KEY FEATURES

- All the features of a standard Jade Counter but with a depth of just 500mm
- Foodsafe stainless steel exterior and aluminium interior
- Integral 'easy grab' door handle
- Self closing doors
- Barrel locked doors
- Magnetic balloon door gaskets with 100% tight seal
- Fitted with 2 2/3GN nylon coated wire shelves per section as standard or trayslides to accommodate 2/3GN containers
- Anti-tilt trayslides
- Removable racking system
- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential).
- Heavy duty, non-marking swivel castors with brakes
- Removable refrigeration system designed for easy service and maintenance
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 43°C ambient
- Fully automatic air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor
- High performance helium leak testing
- Connection to third party supervisory communication systems such as BMS is possible using proprietary equipment. Please contact Williams for more information.

OPTIONS

- Stainless Steel interior
- Additional shelving / trayslides
- Adjustable legs in lieu of castors (add 10mm to height)



JADE SLIMLINE COUNTERS TECHNICAL DATA

	HJSC2	LJSC2	HJSC3	LJSC3
Temperature (°C)	+1/+4°C	-18/-22°C	+1/+4°C	-18/-22°C
Climate Class	Class 4 (30°C)	Class 4 (30°C)	Class 4 (30°C)	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph			
Fuse (Amps)	13	13	13	13
Defrost	Automatic Off Cycle	Automatic Hot Gas	Automatic Off Cycle	Automatic Hot Gas
Noise level (dBA)	63	61	63	61

Fittings

Shelves	4	4	6	6
Trayslides per door	4	4	4	4

Electrical / Energy Data - Hydrocarbon Refrigerant

Refrigerant	R290	R290	R290	R290
Energy Efficiency Class	B	D	B	D
Energy Consumption (kW / 24hrs)*	1.59	5.81	2.07	6.59
Start Up (Amps)	6.6	14.2	6.6	14.2
Running (Amps)	1.07	2.69	1.07	2.69
Heat Rejection (Watts)**	692	623	692	623

IMPORTANT NOTES:

*Energy consumption is tested to EN16825 in 24hrs

***Evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

