

Induction Range 900mm wide

OE8017

- 4 x 5kW induction zones with 270mm diameter cooking area
- Automatic pan detection function cuts power when no pan is present, preventing harm to users, while saving energy
- 6mm thick high impact resistant glass ceramic surface will withstand hard knocks and is easy to clean
- Multiple internal cooling fans and overheat protection for long service life
- 4kW fan assisted oven





OE8017

Induction Hob Features

- 4 x 5kW induction zones with 270mm diameter cooking area
- 6mm thick high impact glass ceramic surface
- Multiple internal cooling fans
- Overheat protection
- Automatic pan detection switches cooking zone off when pan removed
- Heating ON indication
- No pan-present indication
- Error mode indication
- Long life induction system 30,000 hours per zone
- Easy to change air filters

Oven Features

- 4kW heating element
- \bullet Precise thermostatic control from 50 °C to 250 °C
- Fan assisted oven
- Power ON indicator light (green)
- Oven has reached desired temperature indicator light (amber)
- 180° side hinged doors
- Oven capacity 2 x GN1/1
- Heavy-duty easy remove wire chrome rack supports
- 4 position racking with anti tilt guards and safety stops

Cleaning and Servicing

- 6mm thick ceramic glass cooking surface, easy clean, spillages can just be wiped away
- Easy clean stainless steel external finish
- Sits flush to the wall, reducing dirt ingress over the back
- Heavy-duty easy remove wire chrome rack supports
- Stainless steel oven lining with removable base liner
- Access to most parts from the front and top of unit
- Easy change generator air filter

Overall Construction

- Permanent laser etched markings on fascia and knobs
- Fully framed 1.2mm steel chassis
- 1.2 mm stainless steel base panel
- 0.8 mm stainless steel side panels
- Castors as standard
- Sits flush to the wall, recess for service

Induction Hob Construction

• 1.2 mm stainless steel welded bull nose and hob surround

Oven Construction

- 0.8 mm stainless steel outer door skin
- Reinforced door seal
- Double insulated doors and side panels
- Stainless steel oven liner

Inclusive Accessories

• 2 chrome plated shelves



Available Options

- Adjustable legs
- Reduced power options available on request


Available Accessories


• FI41 Filter kit




Technical Data

	OE8017
Width (mm)	900
Depth (mm)	800
Overall height (mm)	900
Hob height (mm)	900
Usable oven capacity h x w x d (mm)	419 x 480 x 510
Oven shelf size w x d (mm)	480 x 510
Hob	4 zones
Fan	Single fan
Hob rating per induction zone (kW)	5.0
Oven rating (kW)	4.0
Total electrical power rating (kW)	24
Electrical supply 3N~+E 400V 50-60Hz Current Rating (Amps)	L1 = 34.8 L2 = 34.8 L3 = 34.8
Net weight (kg)	180
Packed weight (kg)	194
Shipping volume (m3)	1.2
IPX Protection	IPX4

















WK Sales e-mail: sales@lincat.co.uk

■ International Sales Tel: +44 1522 503250
■ International Sales e-mail: export@lincat.co.uk







